



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
Box Cameras	SUPREME	IP9165-HT-v2	Box Camera, 2M 60fps, H.265/H.264/MJPEG, remote back focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9165-LPC-v2	License plate capture, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9165-LPR-v2 Kit (Street)	License plate recognition kit, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, manual focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, Snap-in IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
	V-Series	IP9181-HT-v2	Box Camera, 5M 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	V-Series	IP9181-LPC-v2	License plate capture, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	V-Series	IP9181-LPC-v2 (Kit)	License plate capture kit, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, External IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
	SUPREME	IP9191-HT-v2	Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
	SUPREME	IP9191-LPC-v2	License Plate Capture, Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
Bullet Cameras	SUPREME	IB9365-EHT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~60° C (-58° F ~ 140° F)
	SUPREME	IB9365-HT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	SUPREME	IB9365-HT-A(12-40MM)	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f12 ~ 40mm Motorized Lens, P-iris, IR 100m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	SUPREME	IB9365-EHTV-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	V-Series	IB9367-EHT-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	IB9367-EHT-v2 (5-50mm)	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.8 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	C-Series	IB9368-HT	Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IB9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm or 3.6mm, IR 30m, Smart motion, PoE/DC12V, Working Temperature: -30° C ~ 50° C (-22° F ~ 122° F)
	C-Series	IB9380-H	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IB9387-EHT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	V-Series	IB9387-HT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IB9388-HT	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IB9389-EH-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	IB9389-EHT-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	IB9387-EHTV-V3(12-40MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 12-40mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
Bullet Cameras	V-Series	IB9387-EHTV-V3(7-22MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
	V-Series	IB9387-EHTV-V3(2.7-13.5MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
	SUPREME	IB9391-EHTV-v2	Outdoor Vandal-proof Bullet, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
	V-Series	IB9387-LPR-v2	License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IB9387-LPR-v2-W	License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IB9383-HV	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55° C (-22° F ~ 131° F)
	C-Series	IB9383-HTV	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55° C (-22° F ~ 131° F)
Fixed Dome Cameras	C-Series	FD9166-HN(2.8MM)	Indoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
	C-Series	FD9166-HN(3.6MM)	Indoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
	V-Series	FD9167-HT-v2	Indoor Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~50°C (14°F ~ 122°F)
	C-Series	FD9182-H	Recessed design dome,5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/ N, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C~ 50°C (-10°F ~ 122°F)
	V-Series	FD9187-HT-A	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 45° C (14° F ~ 113° F)
	SUPREME	FD9365-EHTV-A	Outdoor Vandal Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	SUPREME	FD9365-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
	C-Series	FD9366-HV(2.8MM)	Outdoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
	C-Series	FD9366-HV(3.6MM)	Outdoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
	V-Series	FD9367-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
	C-Series	FD9368-HTV	Outdoor Vandal Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm,IR 30m, Smart motion ,PoE/DC12V, Built in Mic, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
	C-Series	FD9380-H	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9380-H(2.8MM)	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
V-Series	FD9387-EHTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~60° C (-58° F ~ 140° F)	



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
Fixed Dome Cameras	V-Series	FD9387-HTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	FD9388-HTV	Outdoor Vandal Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	FD9189-H-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 50° C (14° F ~ 122° F)
	V-Series	FD9189-HT-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 50° C (14° F ~ 122° F)
	V-Series	FD9389-EHV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature:-40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	FD9389-EHTV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	SUPREME	FD9391-EHTV-v2	Outdoor Vandal-proof Dome, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, Smart IR III, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
	INSIGHT	FD9392-EHTV-O	8MP, 50M IR, Edge AI, Driven by OSSA, Azena OS, IP67, IK10
	SUPREME	CD9381-HNTV	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.8~8mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10° C ~ 55° C (14° F ~ 122° F)
	SUPREME	CD9381-HNVF2	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.4mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10° C ~ 55° C (14° F ~ 122° F)
	C-Series	IT9360-H	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9360-H(2.8MM)	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9380-H	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9380-H(2.8MM)	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	C-Series	IT9388-HT	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	V-Series	IT9389-H-v2	Turret Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature:-20° C ~ 50° C (-4° F ~ 122° F)
	V-Series	FD9387-EHTV-V3(7-22MM)	Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	FD9387-EHTV-V3(2.7-13.5MM)	Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40° C ~ 60° C (-40° F ~ 140° F)
	V-Series	FD9187-HT-V3(2.7-13.5MM)	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10° C ~ 50° C (14° F ~ 122° F)
	V-Series	FD9187-HT-V3(7-22MM)	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10° C ~ 50° C (14° F ~ 122° F)
C-Series	FD9383-HV(2.8MM)	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55° C (-22° F ~ 131° F)	
C-Series	FD9383-HV(3.6MM)	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55° C (-22° F ~ 131° F)	
C-Series	FD9383-HTV	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55° C (-22° F ~ 131° F)	



## VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
180° Cameras	C-Series	CC9160-H	Indoor, 2M 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.66mm, fisheye lens, Daytime, PoE, built-in mic, DI/DO, operating temp (-10°C ~ 45°C)
	C-Series	CC9160-H(HS)	Indoor, 2M 180° Panoramic height strip(feet, cm), 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C)
	C-Series	CC9160-H(DJ)	Indoor, 2M 180° Panoramic Door Jamb, 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C)
	C-Series	CC9380-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
	C-Series	CC9381-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
	V-Series	MS9390-HV-v2	Outdoor Vandal Dome, 8MP 180° Panoramic (2x4M sensors), 30fps, H.265/H.264/MJPEG, f2.8mm lenses, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-40° C ~55° C/ -40°F ~ 131°F)
	V-Series	CC9391-HV	Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F)
	V-Series	CC9390-HV	"Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F)
	V-Series	CC9381-HV-V2	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F)
	V-Series	CC9380-HV-V2	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F)
	SUPREME	MS9321-EHV-V2	Outdoor Vandal Bullet, 18MP 180° Panoramic, (4x5MP sensors), 30fps, H.265/H.264/MJPEG, Day/Night, 30m IR illuminators, WDR Pro 120 dB, Smart VCA, Vision Object Analytics, IP66, IK10, IP6K9K, operating temp. (-40°C ~ 55°C, -40°F ~ 131°F)
360° Cameras	C-Series	FE9180-H-v2	Indoor, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, daytime only, WDR Pro, PoE, Built-in Mic, MicroSD/SDHC/SDXC
	SUPREME	FE9192-H	Recessed Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC
	C-Series	FE9380-HV	Outdoor Vandal Proof, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, D/N, IR 10m, WDR Pro, 3DNR, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp -30°C ~ 60°C / -22 °F ~ 140 °F
	SUPREME	FE9382-EHV-v2	Outdoor Vandal Proof, 6M, 30fps, H.265/H.264/MJPEG, f1.245mm lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 55°C / -40 °F ~ 131 °F), DI/DO/ Audio Cable available by special order (PRR)
	SUPREME	FE9191-H-v2	Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC
	SUPREME	FE9391-EHV-v2	Outdoor Vandal Proof, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 60°C / -40 °F ~ 140 °F), DI/DO/ Audio Cable available by special order (PRR)



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
Multi-Sensor Cameras	SUPREME	MA9322-EHTVL	Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.7~7.7mm motorized lenses, D/N, WDR Pro 120dB, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 50°C/ - 40°F ~ 122°F)
Mobile Dome Cameras	SUPREME	MD8564-EH	Mobile Dome, 2M 30fps, H.264/MJPEG, f3.6mm fixed Lens, IR 15M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IP68, IK10, NEMA 4X, EN50155 TX
	V-Series	MD9560-DH(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	V-Series	MD9560-H(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	V-Series	MD9560-H(3.6MM,HL1)	Mobile Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
	SUPREME	MD9582-H	Mobile Dome, 5M 30fps, H.265, f2.8mm or 3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built-in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT4, EN45545 HL1 or HL3
	SUPREME	MD9584-H	Mobile Dome, 5M 30fps, H.265, f3.6mm fixed Lens, 850nm IR 50M, WDR Pro, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IK68, IK10+, NEMA 4X, EN50155 OT4, EN45545 HL3
Speed Dome Cameras	SUPREME	SD9161-H-v2	Indoor Speed Dome, 2M 30fps, H.265/H.264/MJPEG, 10x Optical Zoom, WDR Pro, 3DNR, PoE/AC 24V/DC 48V, I/O*2/1, Two way audio, MicroSD/SDHC/SDXC
	SUPREME	SD9384-EHL	IR Speed Dome, 5M 30fps, H.265, 30x Optical Zoom, IR 200M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
	SUPREME	SD9368-EHL	IR Speed Dome, 2M 60fps, H.265, 40x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
	SUPREME	SD9394-EHL	IR Speed Dome, 4K 30fps, H.265, 30x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
AI Counting Cameras	SUPREME	SC8131	Stereo People Counting Network Camera, dual image sensors, lens f = 2mm, H.264/ MJPEG, Starting Temperature: 0°C ~ 40°C (32°F ~ 104°F), Working Temperature: -10°C ~ 40°C (14°F ~ 104°F), Installation Height: 240~500 cm (7.9~16.4')
	SUPREME	SC8132	Stereo People Counting Network Camera, dual image sensors, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240 cm (6.2~7.9')
	SUPREME	SC8133	Stereo People Counting Network Camera, dual image sensors, white LED, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240cm (6.2~7.9')
	SUPREME	SC9133	Deep Learning AI Counting Network Camera, Deep Learning AI Detection* for Passenger Classification, White LEDs for Low Lighting Counting, EN50155
	SUPREME	SC9133-RTL	AI Counting Network Camera for Retail, Deep Learning AI Counting, 140° Fiseye FOV for Better Coverage, Flexible Installation Height 2.4 to 10 m



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Series	Model	Description
Split-type Camera System	V-Series	VC9101	Video Core, split-type, H.265,H.264/MJPEG, PoE/DC 8-36V, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, operating temp(-10°C ~ 50°C); work with camera unit (CU series)
Facial Recognition Devices	Tablet	FT9361-R	Facial Recognition Access Control Tablet, Linux OS, Memory: 8GB ROM 1GB RAM, Max. 50,000 profiles, 1080P camera, 1440x720 display, PoE Class 4/DC 12V, Weigand
	Facial Recognition CMS	IE9281-FM	Content Management System Support up to 256 Devices in One Single Server Support of Local Display via HDMI Easy to Integrate into Your System Rich Infographic Reports Support Rackmount Installation
	Facial Recognition Workstation	IE9232-F	Mask Detection and Recognition Enroll a Person's Profile with up to 5 Pictures Real-time Notifications and Alerts Persons of Interest (POI) Management Comprehensive Reports Support up to 6 Cameras/Servers
	Facial Recognition Camera	FD9387-FR-v2	5MP, Short Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II
	Facial Recognition Camera	FD9387-FR-v3	5MP, Mid Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II
AI Box	INSIGHT	IE9111-O	NDAA, AI-Box, Edge AI Device, Driven by OSSA, Azena OS, VCA
	INSIGHT	IE9111-O (M12)	NDAA, AI-Box, Edge AI Device, Driven by OSSA, Azena OS, VCA, M12 Connection
NVRs	C-Series	ND9213P	H.265, 4CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 4/2 alarm in/out, 1HDD, 1 LAN(FE), 4 PoE, NDAA
	V-Series	ND9323P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 8 PoE
	V-Series	ND9425P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE
	V-Series	ND9442P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
	V-Series	ND9542P	H.265, 32CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
	SUPREME	NR9581-v2	H.265, 32CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
	SUPREME	NR9681-v2	H.265, 64CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
	SUPREME	NR9682-v2	H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
	SUPREME	NR9782-v2	H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
	SUPREME	NS9521	H.265, 32CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 2 HDD, 2 LAN(Giga), VAST2 Station
	V-Series	ND9326P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 2 LAN(Giga), 8 PoE, Core+ AI
	V-Series	ND9426P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE, Core+ AI
	SUPREME	NR9581-v3	H.265, 32CH(expandable to 128CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 8 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro
	SUPREME	NR9682-v3	H.265, 64CH(expandable to 192CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro





# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Form Factor	Model	Description
PoE	EPoC	AP-FEX-0100-R	EPoC PoE in Rx Module, 1x BNC, 1x FE RJ45, -20 ° C~60 ° C
	EPoC	AP-FEX-0105-D,USA	EPoC Extender DC kit, AP-FEX-0105-R + AP-FEX-0105-T + AA-420, USA
	EPoC	AP-FEX-0105-P	EPoC Extender PoE kit, AP-FEX-0100-R + AP-FEX-0105-T
	EPoC	AP-FEX-0105-R,USA	EPoC DC in Rx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C, AA- 420, USA
	EPoC	AP-FEX-0105-T	EPoC DC in Tx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C
	EPoC	AP-FEX-0150-T	EPoC Outdoor Tx Module, 1x BNC, 1x FE RJ45, -40 ° C~60 ° C, IP67, IK10
	EPoC	AP-FEX-0200-T	EPoC Tx Module, 1x BNC, 2x FE RJ45, -20 ° C~60 ° C
	EPoC	AP-FEX-0250-T	EPoC Outdoor Tx Module, 1x BNC, 2x FE RJ45, -40 ° C~60 ° C, IP67, IK10
	Extender	AP-GXC-0150	1-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
	Extender	AP-GXC-0250	2-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C
	Extender	AP-GXC-0100	1-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
	Extender	AP-GXC-0200	2-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C
	Industrial Solution	AW-IHT-0800	Industrial 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 120W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-1000	Industrial 8xGE PoE + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 240W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-1271	Industrial VivoCam L2+ Managed PoE Switch 8xGE PoE + 4xGE SFP Per PoE port Max. 30W, power budget 240W, 48~57VDC input, -40° C to 75° C
	Industrial Solution	AW-IHS-0202	Industrial Media Convert SFP True Mini Industrial Media Converter, 10/100M RJ45 to 100M SFP, Designed for outdoor CAM enclosure, Din-Rail mount and Panel mount, 18-36VAC/12- 60VDC, -40° C to 75° C
	Industrial Solution	AW-IHT-0601	Industrial 4XGE POE+2XGE SWITCH SFP 12V-56V Super Voltage Booster 12~56VDC input, 4 port 802.3at 30W POE 10/100/1000M + 1 port 10/100/1000M SFP/TX Combo + 1 port 100/1000M SFP, -40° C to 75° C
	Industrial Solution	AW-IHT-0602	Industrial EN50155 4xFE M12 PoE + 2xFE M12 Switch 4 port 802.3at 30W POE M12 10/100M + 1 port M12 10/100M, 24~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHB-0100	Industrial Gigabit 802.3bt 90W PoE injector, 48-56VDC input, -40° C to +75° C
	Industrial Solution	AW-IHB-0400	Industrial 2xGE 802.3bt 90W PoE + 2xGE SFP Switch, power budget 180W, 48~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHB-0800	Industrial 4xGE 802.3bt 90W PoE + 2xGE UTP + 2xGE SFP Switch, power budget 360W, 54~56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHB-1040	Industrial Lite Managed PoE Switch 2xGbE bt 90W + 6xGbE af/at 30W + 2xGbE SFP, Power budget 300W, 48-56VDC input, -40° C to 75° C
	Industrial Solution	AW-IHT-1002	Industrial M12 PoE Switch 8xFE D-coded PoE + 2xGbE X-coded, EN50155/ EN45545-2, -40° C to 75° C
	Injector	AP-GIC-011A-030	Indoor Gigabit IEEE 802.3at 30W PoE Injector
	Injector	AP-GIC-011B-090	Indoor Gigabit IEEE 802.3bt 90W PoE Injector
	Managed Switch	AW-GEV-104B-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE O utput Power Max. 130W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-107A-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 130W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-184B-250,USA	16-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 250W) Integrate with VIVOTEK Camera for surveillance application
	Managed Switch	AW-GEV-264B-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 370W) Integrate with VIVOTEK Camera for surveillance application



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Form Factor	Model	Description
PoE	Managed Switch	AW-GEV-267A-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 370W) Integrate with Vivotek Camera for surveillance application
	Managed Switch	AW-GTS-287A,USA	24xGE SFP + 4xCombo GE + 4x 10G SFP+ L2 Plus Managed Switch
	Managed Switch	AW-GEV-108A-130	VIVOCAM L2 Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 2xGbE Combo + 1xRJ45 console port, Power Budget 130W
	Managed Switch	AW-GEV-288A-370	VIVOCAM L2 Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 4xGbE Combo + 1xRJ45 Console port, Power Budget 370W
	Managed Switch	AW-GEL-065A-060	Lite Managed PoE Switch 4xGbE PoE + 2xGbE RJ45, Power Budget 60W
	Managed Switch	AW-GEL-105A-110	Lite Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 1xGbE RJ45 + 1xGbE SFP, Power Budget 110W
	Managed Switch	AW-GEL-205A-260	Lite Managed PoE Switch 4xGbE bt 90W PoE + 12xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 260W
	Managed Switch	AW-GEL-285A-380	Lite Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 380W
	Optical Transceiver	SFP-1000-CPTX-X1	Gigabit SFP to RJ45 Module
	Optical Transceiver	SFP-1000-CPTX-X1I	Industrial Gigabit SFP to RJ45 Module
	Optical Transceiver	SFP-1000-MM13-02	Gigabit Mini GBIC Multi Mode 1310nm 2KM, LC Connector
	Optical Transceiver	SFP-1000-MM13-02I	Industrial Gigabit Mini GBIC Multi Mode 1312nm 2KM, LC Connector
	Optical Transceiver	SFP-1000-MM85-X5	Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector
	Optical Transceiver	SFP-1000-MM85-X5I	Industrial Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-10	Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-10I	Industrial Gigabit Mini GBIC Single Mode 1312nm 10KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-40	Gigabit Mini GBIC Single Mode 1310nm 40KM, LC Connector
	Optical Transceiver	SFP-1000-SM13-40I	Industrial Gigabit Mini GBIC Single Mode 1312nm 40KM, LC Connector
	Optical Transceiver	SFP-2000-MM85-X3	10 Gigabit Mini GBIC Multi Mode 850nm 0.3KM, LC Connector
	Optical Transceiver	SFP-2000-SM13-10	10 Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
	Outdoor Cabinet	AT-CAB-001	Cabinet IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover is included.
	Outdoor Cabinet	AT-CAB-002	Side-mount bracket for HLG series power supply Protects accessory devices such as 120W power supply.
	Outdoor Cabinet	AT-CAS-001	Cabinet for Speed dome IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover






# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Form Factor	Model	Description
PoE	Outdoor Cabinet	AT-DRB-001	Cabinet industrial 95W PoE switch AW-IHH-0800 bracket
	Outdoor Cabinet	AT-PSP-001	PoE Surge Protector: 8-10KA AT-PSP-001 is a surge protection device to provide Signal/Power path and surge protection capability. It employed our patented surge blocker with shunt devices and parallel devices to guarantee the safety of your device, ev
	Outdoor Cabinet	AT-SUN-001	Sunshield for AT-CAx series cabinet Metal sunshield for Vivotek Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation.
	Outdoor Cabinet	AT-SUN-002	Sunshield for AT-CAx + AT-CAB-002 cabinet Metal sunshield for BOTH Vivotek Cabinet and DC Power cabinet. Reduces the temperature inside the cabinet, caused by sun radiation.
	Outdoor Cabinet	AT-SWH-000	Power Safety Kit (100~275VAC): 20-40KA Electrical safety kit for Vivotek Cabinet in countries where the mains power is 275V AC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.
	Outdoor Cabinet	AT-SWH-002	Door open/close detection switch Intrusion door switch for Vivotek Cabinet, connection to I/O port.
	Outdoor Cabinet	AT-WPC-001	Cable gland M16 CABLE GLAND 4~7mm AWG 6PCS
	Outdoor Cabinet	AT-WPC-002	Cable gland M16 CABLE GLAND for Corrugated Tubing : 5/16 " 6PCS
	Outdoor Surger	AP-PSP-050	Outdoor PoE Surge Protector 16KV surge Operating temperature from -40° C to 85 ° C
	Outdoor Switch	AW-GEH-043A-120	Outdoor Unmanaged 2xGE 95W PoH/PoE + 2xGE SFP Switch, Per PoE port max. 95W, power budget 120W, IP67, IK10
	Outdoor Switch	AW-GET-083A-120	Outdoor Unmanaged 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port max. 30W, power budget 120W, IP67, IK10
	Power Supply	HLG-120H-24	90~305VAC In ,24VDC/120Wut ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-120H-48	90~305VAC In ,48VDC/120W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-120H-54	90~305VAC In ,54VDC/120W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-240H-54	90~305VAC In ,54VDC/240W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-60H-24	90~305VAC In ,24VDC/60Wut ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-24	90~305VAC In ,24VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-48	90~305VAC In ,48VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	HLG-80H-54	90~305VAC In ,54VDC/80W Out ,IP67, - 40 °C ~ 70 °C
	Power Supply	DRL-48V120W1EN	90~264VAC In, 48VDC/120W Out , - 30 °C ~ 70 °C
Power Supply	DRL-48V240W1EN	90~264VAC In, 48VDC/240W Out , - 30 °C ~ 70 °C	



# VIVOTEK - TAA Compliant Product List

October 17, 2024


Category	Form Factor	Model	Description
PoE	Unmanaged Switch	AW-FET-060C-065	4xFE POE +2FE UTP Switch
	Unmanaged Switch	AW-FGT-100D-120	8xFE PoE + 2xGE Combo Switch
	Unmanaged Switch	AW-FGT-180D-250	16xFE POE +2G COMBO Switch
	Unmanaged Switch	AW-FGT-260D-380	24xFE POE +2G COMBO Switch
	Unmanaged Switch	AW-FET-060D-065	4xFE PoE + 2xFE RJ45 Unmanaged Switch, Power Budget 65W
	Unmanaged Switch	AW-FGT-180F-250	16xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 250W
	Unmanaged Switch	AW-FGT-260F-380	24xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 380W
Accessory	Enclosure	AE-238	Side Open Aluminum Camera Housing AC24V in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
	Enclosure	AE-239	Side Open Aluminum Camera Housing PoE in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
	Enclosure	AE-243	Side Open Aluminum Camera Housing, AC24V in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
	Enclosure	AE-244	Side Open Aluminum Camera Housing, PoE in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
	Enclosure	AE-23A	Side Open Aluminum Camera Housing AC24V in,Window heater, Fan,IP68, -20~50°C , optional snap-in VAIR,Wall bracket, Sun shield
	Enclosure	AE-23E-v2	Side Open Aluminum Camera Housing, PoE in (BT), Window heater, Fan, IP68, -20~65 °C , optional snap-in VAIR, Wall bracket, Sun shield
	CaMate	CA80I8-1040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
	CaMate	CA80I8-2040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
	CaMate	CM32I8-010	IR illuminator fixed IR 10°,180m, 32w
	CaMate	CM32I8-035	IR illuminator fixed IR 35°,60m, 32w
	CaMate	CM48I8-1040	IR illuminator with CVA, 10°~ 40°, 100~250m, 48w
	CaMate	CM48I8-180	IR illuminator with CVA, 180°, 40m, 48w
	CaMate	CM48I8-2040	IR illuminator with CVA, 20°~ 40°, 120 ~ 200m, 48w
	CaMate	CM48I8-4080	IR illuminator with CVA, 40°~ 80°, 60~90m, 48w
CaMate	CM48I8-90120	IR illuminator with CVA, 90°~ 120°, 45~55m, 48w	



## VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Form Factor	Model	Description
EOL Models	Bullet	IB9360-H	Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	Cube	CC8160 (HS,BLACK,CM)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), black color
	Cube	CC8160 (HS,BLACK,FEET)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), black color
	Cube	CC8160 (HS,SILVER,CM)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), silver color
	Cube	CC8160 (HS,SILVER,FEET)	Indoor, 2M 180° Panoramic height strip, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), silver color
	Cube	CC8160 (W/KIT)	Indoor, 2M 180° Panoramic, 30fps, H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, built-in mic, operating temp (0°C ~ 40°C / 32 °F ~ 104 °F), flat mount
	Cube	CC8370-HV	Outdoor Vandal Dome, 3M 180° Panoramic, 30fps, H.264/MJPEG, f1.6mm fisheye lens, Daytime, WDR Pro, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20°C ~ 50°C/ -4°F ~ 122°F)
	Split	VC8101,(CU8161-H)	Split-type, 2M 30fps, H.264/MJPEG, f3.7 mm fixed Lens, WDR Pro, 3DNR, PoE/DC 8-36V, 5 Meters cable, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC
	Split	VC8101,(CU8163-H)	Split-type, 2M 30fps, H.264/MJPEG, f1.6 mm fixed Lens, 180° Panoramic View, WDR Pro, 3DNR, PoE/DC 8-36V, 5 Meters cable, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC
	Fisheye	FE8182	Recessed Indoor, 5M, 15fps, H.264/MJPEG, f1.05mm fisheye lens, Daytime, WDR Enhanced, PoE, built-in mic, MicroSD/SDHC/SDXC
	Corner Camera	CD8371-HNTV(METAL)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8~8mm Motorized lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14°F ~ 131°F)
	Corner Camera	CD8371-HNTV(WHITE)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8~8mm Motorized lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14°F ~ 131°F)
	Corner Camera	CD8371-HNVF2(METAL)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8mm lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14 °F ~ 131°F)
	Corner Camera	CD8371-HNVF2(WHITE)	Indoor/Outdoor Vandal Proof, 3M, 20fps, H.264/MJPEG, f2.8mm lens, D/N, 940nm IR up to 10m, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10+, operating temp (-10°C ~ 55°C/ 14 °F ~ 131°F)
	Mini Dome	FD8166A	Indoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, WDR Enhanced, 3DNR, PoE, I/O*1/0, One way audio,Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD8166A-N	Indoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, 940IR 6m, WDR Enhanced, 3DNR, PoE, One way audio, Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD816CA-HF2	Indoor Extra mini Dome, Recessed mount, 2M 30fps, H.264/MJPEG, f2.8mm fixed lens, SNV, WDR PRO,3DNR, PoE, Built-in microphone, MicroSD/SDHC/SDXC
	Mini Dome	FD8366-V	Outdoor Mini Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, 850nm IR 15M, 3DNR, PoE, I/O*1/0, One way audio, Built-in microphone, MicroSD/SDHC/SDXC
	Fixed Dome	FD8177-HT	Indoor Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
	Fixed Dome	FD8377-EHTV	Outdoor Vandal Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IK10, Working Temperature: -50°C ~ 50°C (-58°F ~ 122°F)
	Fixed Dome	FD8377-HTV	Outdoor Vandal Dome, 4M 30fps, H.264/MJPEG, f2.8 ~ 12mm Motorized Lens, P-iris, D/N, IR 30m, SNV, WDR PRO, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IK10, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
	Fixed Dome	FD9360-H	Outdoor Fixed Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
	Mobile Dome	MD8531H	Mobile Dome, 1M 30fps, H.264/MJPEG, f3.6/f4.2mm fixed Lens, WDR Pro, 3DNR, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP66, IK10, extreme weather (-25°C ~ 55°C/-13°F ~ 131°F), EN50155 T1
	Mobile Dome	MD8563-DEH	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP67, IK10, EN50155 TX
	Mobile Dome	MD8563-EH	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/f3.6mm fixed Lens, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP67, IK10, EN50155 TX
	Mobile Dome	MD8565-N	Mobile Dome, 2M 30fps, H.264/MJPEG, f2.8mm/3.6mm fixed Lens, 940nm IR 10M, WDR Pro, 3DNR, M12, PoE, I/O*1/0, One way audio, Built-in microphone, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, EN50155 T1



# VIVOTEK - TAA Compliant Product List

October 17, 2024

Category	Form Factor	Model	Description
EOL Models	Rackmount NVR	NR9581,MAE,(32CH,ELABEL)	H.265, 32CH, 1 HDMI+1 VGA+ 1 DP+ 1 DVI, 1080P @ 150 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9681,MAE,(64CH,ELABEL)	H.265, 64CH, 1 HDMI+1 VGA+ 1 DP+ 1 DVI, 1080P @ 150 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9682	H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Rackmount NVR	NR9782	H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power
	Video Server	VS8100-v2	Video server, 1CH, D1 30pfs, H.264, MJPEG, DC 12V, One-way Audio