

| Product Type | Model | Description |
|-----------------------------|------------------|--|
| 110 – Network Camera – Dome | FD9166-HN(2.8MM) | Indoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro |
| 110 – Network Camera – Dome | FD9166-HN(3.6MM) | Indoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro |
| 110 – Network Camera – Dome | FD9167-HT-v2 | Indoor Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9182-H | Recessed design dome,5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/ N, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10° C~ 50°C (-10°F ~ 122°F) |
| 110 – Network Camera – Dome | FD839-EHTV-v2 | VORTEX Premium Series Outdoor Vandal Remote Dome, 5M 15fps, H.264/MJPEG, f = 2.8~12 mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), NEMA 4X/IP66/IK10/Working Temperature:-35°C ~ 50°C (-31°F ~ 122°F),Built-in microphone |
| 110 – Network Camera – Dome | FD939-EHTV | VORTEX Premium Series Outdoor Vandal Remote Dome, 8M 15fps, H.264/MJPEG, f = 4.3~9.8mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), NEMA 4X/IP66/IK10/Working Temperature:-35°C ~ 50°C (-31°F ~ 122°F),Built-in microphone |
| 110 – Network Camera – Dome | FD9187-HT-A | Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 45° C (14° F ~ 113° F) |
| 110 – Network Camera – Dome | FD9365-EHTV-A | Outdoor Vandal Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two- way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9365-EHTV-v2 | Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/ NEMA 4X, Working Temperature: -50° C ~ 60°C (-58°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9366-HV(2.8MM) | Outdoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic |
| 110 – Network Camera – Dome | FD9366-HV(3.6MM) | Outdoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic |
| 110 – Network Camera – Dome | FD833-HV | VORTEX Premium Series Outdoor Vandal Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-30°C ~ 55°C (-22°F ~ 131°F) |
| 110 – Network Camera – Dome | FD9367-EHTV-v2 | Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9368-HTV | Outdoor Vandal Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9369 | 2M 30fps, H.265/H.264/MJPEG, 2.8mm,IR 30m, Smart motion ,PoE/DC12V, Built in Mic, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9380-H | Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9380-H(2.8MM) | Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9387-EHTV-A | Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~60° C (-58° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9387-HTV-A | Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |

| | | |
|-----------------------------|----------------|---|
| 110 – Network Camera – Dome | FD9388-HTV | Outdoor Vandal Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 110 – Network Camera – Dome | FD9189-H-v2 | Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9189-HT-v2 | Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9389-EHV-v2 | Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9389-EHTV-v2 | Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9189-H-V3 | Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 30m, HDMI output, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, Working Temperature: 0°C ~ 45°C (-32°F ~ 113°F) |
| 110 – Network Camera – Dome | FD9389-EHV-V3 | Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optioanl accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9389-EHTV-V3 | Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.3~9.7mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optioanl accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9199-H | Indoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 30m, HDMI output, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optioanl accessory, MicroSD/SDHC/SDXC, Working Temperature: 0°C ~ 45°C (-32°F ~ 113°F) |
| 110 – Network Camera – Dome | FD9399-EHV | Outdoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optioanl accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9399-EHTV | Outdoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.3~9.8mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optioanl accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9391-EHTV-v2 | Outdoor Vandal-proof Dome, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, Smart IR III, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/ IK10/NEMA 4X, Working Temperature: -50° C ~ 60°C (-58°F ~ 140°F) |
| 110 – Network Camera – Dome | CD9381-HNTV | Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.8~8mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | CD9381-HNVF2 | Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.4mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F) |

| | | |
|-------------------------------|----------------------------|---|
| 110 – Network Camera – Dome | FD9387-EHTV-V3(7-22MM) | Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9387-EHTV-V3(2.7-13.5MM) | Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD9187-HT-V3(2.7-13.5MM) | Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9187-HT-V3(7-22MM) | Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two- way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD9383-HV(2.8MM) | Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) |
| 110 – Network Camera – Dome | FD9383-HV(3.6MM) | Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) |
| 110 – Network Camera – Dome | FD9383-HTV | Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) |
| 110 – Network Camera – Dome | FD9186-H | Indoor Mini Dome, 5M 30fps, H.265, f2.8mm fixed lens, 3 Axis adjustment, IR 30M, WDR Pro, 3DNR, PoE, One way audio, Built-in microphone, DI*1, DC jack, MicroSD/SDHC/SDXC |
| 110 – Network Camera – Dome | FD639 | VORTEX Essential Series Outdoor Vandal Dome, 2M 15fps, H.264/MJPEG, 2.8mm, D/N, IR 30m, WDR Enhance, Smart Stream III, 3DNR, PoE/DC12V, Built in Mic, Built-in 128G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 50°C (-22°F ~ 122° F) |
| 110 – Network Camera – Dome | FD819-H | VORTEX Essential Series Indoor Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD819-HT | VORTEX Essential Series Indoor Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 110 – Network Camera – Dome | FD839-EHV | VORTEX Essential Series Outdoor Vandal Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD839-EHTV | VORTEX Essential Series Outdoor Vandal Vari-focal Dome, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 110 – Network Camera – Dome | FD837-HTV | VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 5M 15fps, H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IP67/IK10, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9360-H | Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 111 – Network Camera – Turret | IT9360-H(2.8MM) | Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |

| | | |
|-------------------------------|-----------------|---|
| 111 – Network Camera – Turret | IT9380-H | Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30 ° C ~ 60° C (-22° F ~ 140° F) |
| 111 – Network Camera – Turret | IT9380-H(2.8MM) | Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 111 – Network Camera – Turret | IT9388-HT | Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 111 – Network Camera – Turret | IT9389-H-v2 | Turret Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9383-HVW | Flat-faced AI Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9383-HTVW | Flat-faced AI Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 111 – Network Camera – Turret | IT839-H | VORTEX Essential Series Turret, 5M 15fps, H.264/MJPEG, f2.8mm Fixed-focal Lens, D/N, IR 30m, SNV, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK08/Working Temperature: -20°C ~ 50°C (-4° F ~ 122° F) |
| 111 – Network Camera – Turret | IT833-HVW | VORTEX Premium Series Outdoor Vandal Fixed Turret, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR/warm light 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F), Built-in microphone |
| 111 – Network Camera – Turret | IT9399-HVW | Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, f4.2mm fixed focal lens, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9399-HTVW | Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, motorized lens 4.3~9.8mm, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9389-HVW-V3 | Flat-faced AI turret, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 111 – Network Camera – Turret | IT9389-HTVW-V3 | Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, motorized lens 2.8~12mm, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 120 – Network Camera – Bullet | IB839-EHTV-v2 | VORTEX Premium Series Outdoor Vandal Remote Bullet, 5M 15fps, H.264/MJPEG, f = 2.8~12 mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -35°C ~ 50°C (-31°F ~ 122°F), Two-way audio, Built-in microphone |
| 120 – Network Camera – Bullet | IB939-EHTV | VORTEX Premium Series Outdoor Vandal Remote Bullet, 8M 15fps, H.264/MJPEG, f = 4.3~9.8mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -35°C ~ 50°C (-31°F ~ 122°F), Two-way audio, Built-in microphone |
| 120 – Network Camera – Bullet | IB833-HV | VORTEX Premium Series Outdoor Vandal Fixed Bullet, 5M 15fps, H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F), Built-in microphone |
| 120 – Network Camera – Bullet | IB9389-EHV-V3 | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9389-EHTV-V3 | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 3.3~9.7mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |

| | | |
|-------------------------------|-------------------------|---|
| 120 – Network Camera – Bullet | IB9399-EHV | Outdoor Bullet, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9399-EHTV | Outdoor Bullet, 8M 30fps, H.265/H.264/MJPEG, 4.3~9.8mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9365-EHT-A | Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~60° C (-58° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9365-HT-A | Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9365-HT-A(12-40MM) | Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f12 ~ 40mm Motorized Lens, P-iris, IR 100m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9365-EHTV-v2 | Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/ NEMA 4X, Working Temperature: -50° C ~ 60° C (-58°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9367-EHT-v2 | Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9367-EHT-v2 (5-50mm) | Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9368-HT | Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9369 | 2M 30fps, H.265/H.264/MJPEG, 2.8mm or 3.6mm,IR 30m, Smart motion,PoE/ DC12V, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F) |
| 120 – Network Camera – Bullet | IB9380-H | Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9387-EHT-A | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9387-HT-A | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9388-HT | Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 120 – Network Camera – Bullet | IB9389-EH-v2 | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9389-EHT-v2 | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9387-EHTV-V3(12-40MM) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 12-40mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |

| | | |
|--|----------------------------|--|
| 120 – Network Camera – Bullet | IB9387-EHTV-V3(7-22MM) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9387-EHTV-V3(2.7-13.5MM) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9391-EHTV-v2 | Outdoor Vandal-proof Bullet, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/ IP67/IK10/NEMA 4X, Working Temperature: -50° C ~ 60°C (-58°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB9383-HV | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 55°C (-22°F ~ 131°F) |
| 120 – Network Camera – Bullet | IB9383-HTV | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) |
| 120 – Network Camera – Bullet | IB639 | VORTEX Essential Series Outdoor Bullet, 2M 15fps, H.264/MJPEG, 2.8mm, D/N, IR 30m, WDR Enhance, Smart Stream III, 3DNR, PoE/DC12V, Built in Mic, Built-in 128G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 50°C (-22°F ~ 122° F) |
| 120 – Network Camera – Bullet | IB839-EH | VORTEX Essential Series Outdoor Bullet, 5M 15fps, H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60° C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB839-EHT | VORTEX Essential Series Outdoor Bullet, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| 120 – Network Camera – Bullet | IB837-HT | VORTEX Premium Series (Powerful AI Search) Outdoor Bullet, 5M 15fps, H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IP67/IK10, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| 130 – Network Camera – Fisheye Panoramic | FE9180-H-v2 | Indoor, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, daytime only, WDR Pro, PoE, Built-in Mic, MicroSD/SDHC/SDXC |
| 130 – Network Camera – Fisheye Panoramic | FE9192-H | Recessed Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC |
| 130 – Network Camera – Fisheye Panoramic | FE9380-HV | Outdoor Vandal Proof, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, D/ N, IR 10m, WDR Pro, 3DNR, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp -30°C ~ 60°C / -22 °F ~ 140 °F |
| 130 – Network Camera – Fisheye Panoramic | FE9382-EHV-v2 | Outdoor Vandal Proof, 6M, 30fps, H.265/H.264/MJPEG, f1.245mm lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 55°C / -40 °F ~ 131 °F), DI/DO/ Audio Cable available by special order (PRR) |
| 130 – Network Camera – Fisheye Panoramic | FE9191-H-v2 | Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC |
| 130 – Network Camera – Fisheye Panoramic | FE9391-EHV-v2 | Outdoor Vandal Proof, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 60°C / -40 °F ~ 140 °F), DI/DO/ Audio Cable available by special order (PRR) |
| 130 – Network Camera – Fisheye Panoramic | FE9391-EHV-v2 (1.18MM) | Outdoor 360 Fisheye, 12MP 2816x2816, 30fps, H.265/H.264/MJPEG, f1.18mm lens, F1.8, WDR Pro, 20m Smart IR, Built-in Mic, Optional DI/DO/2-way Audio, MicroSD/SDHC/SDXC, PoE, Smart VCA, IP66, IK10, NEMA 4X, Local Dewarp, NDAA, -40°C ~ 55°C; |
| 130 – Network Camera – Fisheye Panoramic | FE9191-H-V2 (1.18MM) | Indoor 360 Fisheye, 12MP 2816x2816, 30fps, H.265/H.264/MJPEG, f1.18mm lens, F1.8, WDR Pro, Built-in Mic, MicroSD/SDHC/SDXC, PoE, Smart VCA, Local Dewarp, NDAA, IK10, -10°C ~ 50°C |

| | | |
|--|--------------|---|
| 130 – Network Camera – Fisheye Panoramic | FE912-H | VORTEX Premium Series (Powerful AI Search) Indoor Recessed 360 Fisheye, 12M (2944x2944), 15fps, H.264/MJPEG, f1.22mm fisheye lens, F1.8, Day/Night, WDR Pro, Local Dewarp, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), Smart Stream III, Working Temperature: -10° C ~ 50°C (14°F ~ 122°F) |
| 130 – Network Camera – Fisheye Panoramic | FE931-EHV | VORTEX Premium Series (Powerful AI Search) Outdoor Vandal-proof 360 Fisheye, 12M (2944x2944), 15fps, H.264/MJPEG, f1.22mm fisheye lens, F1.8, Day/Night, WDR Pro, Local Dewarp, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), Smart Stream III, Working Temperature: -40° C ~ 60°C (-40°F ~ 140°F) |
| 131 – Network Camera – Compact Panoramic | CC831-HV | VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 5MP 180° Panoramic, 15fps, H.264/MJPEG, f1.47 fisheye lens, Day/Night, 20M IR, WDR Pro, PoE, built-in mic, Built-in 256GB MicroSD Card(30 Days Edge Recording),IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F) |
| 131 – Network Camera – Compact Panoramic | CC830-HV | VORTEX Premium Series (Powerful AI Search)Outdoor Vandal Dome, 5MP 180° Panoramic, 15fps, H.264/MJPEG, f1.47 fisheye lens, Day/Night, WDR Pro PoE, built-in mic, Built-in 256GB MicroSD Card(30 Days Edge Recording) IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F) |
| 131 – Network Camera – Compact Panoramic | CC9160-H | Indoor, 2M 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.66mm,fisheye lens, Daytime, PoE, built-in mic, DI/DO, operating temp (-10°C ~ 45°C) |
| 131 – Network Camera – Compact Panoramic | CC9160-H(HS) | Indoor, 2M 180° Panoramic height strip(feet, cm), 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C) |
| 131 – Network Camera – Compact Panoramic | CC9160-H(DJ) | Indoor, 2M 180° Panoramic Door Jamb, 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C) |
| 131 – Network Camera – Compact Panoramic | CC9380-HV | Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122° F) |
| 131 – Network Camera – Compact Panoramic | CC9381-HV | Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F) |
| 131 – Network Camera – Compact Panoramic | CC9391-HV | Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F) |
| 131 – Network Camera – Compact Panoramic | CC9390-HV | Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F) |
| 131 – Network Camera – Compact Panoramic | CC9381-HV-V2 | Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F) |

| | | |
|--|----------------|--|
| 131 – Network Camera – Compact Panoramic | CC9380-HV-V2 | Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F) |
| 132 – Network Camera – Multi-directional Panoramic | MA9311-EHTV | Outdoor Vandal Dome, 10M Multi-Sensor Adjustable, (2x5M sensors), 30fps, H.265/H.264/MJPEG, 2.8~12mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 20m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131 °F) |
| 132 – Network Camera – Multi-directional Panoramic | MA9312-EHTV | Outdoor Vandal Dome, 16M Multi-Sensor Adjustable, (2x8M sensors), 30fps, H.265/H.264/MJPEG, 4.3~9.8mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 20m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131 °F) |
| 132 – Network Camera – Multi-directional Panoramic | MA9322-EHTV-V2 | Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.2~7.7mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131 °F) |
| 132 – Network Camera – Multi-directional Panoramic | MA9322-EHTVL | Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.7~7.7mm motorized lenses, D/N, WDR Pro 120dB, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 50°C/ - 40 °F ~ 122°F) |
| 133 – Network Camera – Multi-sensor Panoramic | MS9390-HV-v2 | Outdoor Vandal Dome, 8MP 180° Panoramic (2x4M sensors), 30fps, H.265/H.264/ MJPEG, f2.8mm lenses, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built- in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-40° C ~55° C/ -40°F ~ 131°F) |
| 133 – Network Camera – Multi-sensor Panoramic | MS9321-EHV-V2 | Outdoor Vandal Bullet, 18MP 180° Panoramic, (4x5MP sensors), 30fps, H.265/H.264/MJPEG, Day/Night, 30m IR illuminators, WDR Pro 120 dB, Smart VCA, Vision Object Analytics, IP66, IK10, IP6K9K, operating temp. (-40°C ~ 55°C, -40°F ~ 131°F) |
| 133 – Network Camera – Multi-sensor Panoramic | MS930-EHV | VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 8M 180° Panoramic (4736x 1648), (2x4M sensors), 15fps, H.264/MJPEG, 2.8mm each lens, D/N, IR 20m, Smart IR III, WDR Pro, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), IP66, IK10, Operating Temp-40°C ~ 60°C (-40°F ~ 140°F) |
| 140 – Network Camera – PTZ | SD9161-H-v2 | Indoor Speed Dome, 2M 30fps, H.265/H.264/MJPEG, 10x Optical Zoom, WDR Pro, 3DNR, PoE/AC 24V/DC 48V, I/O*2/1, Two way audio, MicroSD/SDHC/SDXC |
| 140 – Network Camera – PTZ | SD9384-EHL | IR Speed Dome, 5M 30fps, H.265, 30x Optical Zoom, IR 200M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X |
| 140 – Network Camera – PTZ | SD9368-EHL | IR Speed Dome, 2M 60fps, H.265, 40x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X |
| 140 – Network Camera – PTZ | SD9394-EHL | IR Speed Dome, 4K 30fps, H.265, 30x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X |
| 150 – Network Camera – Box | IP9165-HT-v2 | Box Camera, 2M 60fps, H.265/H.264/MJPEG, remote back focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio |
| 150 – Network Camera – Box | IP9181-HT-v2 | Box Camera, 5M 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio |

| | | |
|---------------------------------------|-----------------------|--|
| 150 – Network Camera – Box | IP9191-HT-v2 | Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio |
| 160 – Network Camera – Transportation | MD9560-H-V2(2.4 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD9560-H-V2(2.8 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD9560-H-V2(6 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD9560-H-V2(2.8 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD9560-DH-V2 (2.8 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD9560-DH-V2 (3.6 mm) | Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~ 55°C |
| 160 – Network Camera – Transportation | MD8564-EH | Mobile Dome, 2M 30fps, H.264/MJPEG, f3.6mm fixed Lens, IR 15M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IP68, IK10, NEMA 4X, EN50155 TX |
| 160 – Network Camera – Transportation | MD8564-EH-V2 (3.6 mm) | 5MP, 3.6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 4pin D-coded PoE, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+ , NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security |
| 160 – Network Camera – Transportation | MD8564-EH-V2 (6 mm) | 5MP, 6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 4pin D-coded PoE, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+ , NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security |
| 160 – Network Camera – Transportation | MD8564-DEH-V2 (6 mm) | 5MP, 6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 5pin A-coded DC & 4pin D-coded PoE backup, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+ , NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security |
| 160 – Network Camera – Transportation | MD9560-DH(2.8MM,HL1) | Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1 |
| 160 – Network Camera – Transportation | MD9560-H(2.8MM,HL1) | Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1 |
| 160 – Network Camera – Transportation | MD9560-H(3.6MM,HL1) | Mobile Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1 |
| 160 – Network Camera – Transportation | MD9582-H | Mobile Dome, 5M 30fps, H.265, f2.8mm or 3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built-in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT4, EN45545 HL1 or HL3 |
| 160 – Network Camera – Transportation | MD9584-H | Mobile Dome, 5M 30fps, H.265, f3.6mm fixed Lens, 850nm IR 50M, WDR Pro, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IK68, IK10+, NEMA 4X, EN50155 OT4, EN45545 HL3 |
| 160 – Network Camera – Transportation | SC8132 | Stereo People Counting Network Camera, dual image sensors, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240 cm (6.2~7.9') |

| | | |
|---------------------------------------|-------------------------------|---|
| 160 – Network Camera – Transportation | SC8133 | Stereo People Counting Network Camera, dual image sensors, white LED, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240cm (6.2~7.9') |
| 160 – Network Camera – Transportation | SC9133-RTL | AI Counting Network Camera for Retail, Deep Learning AI Counting, 140° Fiseye FOV for Better Coverage, Flexible Installation Height 2.4 to 10 m |
| 162 – Network Camera – Application | FD9387-FR-v2 | 5MP, Short Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II |
| 162 – Network Camera – Application | FD9387-FR-v3 | 5MP, Mid Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II |
| 162 – Network Camera – Application | IB9387-LPR-v2 | License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/ AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 162 – Network Camera – Application | IB9387-LPR-v2-W | License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/ AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F) |
| 162 – Network Camera – Application | VC9101 | Video Core, split-type, H.265,H.264/MJPEG, PoE/DC 8-36V, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, operating temp(-10°C ~ 50°C); work with camera unit (CU series) |
| 162 – Network Camera – Application | SC8131 | Stereo People Counting Network Camera, dual image sensors, lens f = 2mm, H.264/ MJPEG, Starting Temperature: 0°C ~ 40°C (32°F ~ 104°F), Working Temperature: -10°C ~ 40°C (14°F ~ 104°F), Installation Height: 240~500 cm (7.9~16.4') |
| 162 – Network Camera – Application | SC9133 | Deep Learning AI Counting Network Camera, Deep Learning AI Detection* for Passenger Classification, White LEDs for Low Lighting Counting, EN50155 |
| 162 – Network Camera – Application | IB9387-LPR-V3(2.7-13.5MM) (N) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VIVOTEK ANPR, Working Temperature: -40° C ~ 60°C (-40°F ~ 140°F) |
| 162 – Network Camera – Application | IB9387-LPR-V3(2.7-13.5MM) (V) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VaxALPR, Working Temperature: -40°C ~ 60° C (-40°F ~ 140°F) |
| 162 – Network Camera – Application | IB9387-LPR-V3(7-22MM) (N) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, , EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VIVOTEK ANPR, Working Temperature: -40° C ~ 60°C (-40°F ~ 140°F) |
| 162 – Network Camera – Application | IB9387-LPR-V3(7-22MM) (V) | Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, , EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VaxALPR, Working Temperature: -40°C ~ 60° C (-40°F ~ 140°F) |
| 162 – Network Camera – Application | IP9165-LPC-v2 | License plate capture, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio |

| | | |
|------------------------------------|----------------------------|---|
| 162 – Network Camera – Application | IP9165-LPR-v2 Kit (Street) | License plate recognition kit, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, manual focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/ DC12V/AC24V, I/O 2*2, RS485, 2way audio, Snap-in IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F) |
| 162 – Network Camera – Application | IP9181-LPC-v2 | License plate capture, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/ DC12V/AC24V, I/O 2*2, RS485, 2way audio |
| 162 – Network Camera – Application | IP9181-LPC-v2 (Kit) | License plate capture kit, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/ DC12V/AC24V, I/O 2*2, RS485, 2way audio, External IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F) |
| 162 – Network Camera – Application | IP9191-LPC-v2 | License Plate Capture, Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio |
| 200 – NVR – Embedded | ND9213P | H.265, 4CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 4/2 alarm in/out, 1HDD, 1 LAN(FE), 4 PoE, NDAA |
| 200 – NVR – Embedded | ND9323P | H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 8 PoE |
| 200 – NVR – Embedded | ND9425P | H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE |
| 200 – NVR – Embedded | ND9442P | H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI |
| 200 – NVR – Embedded | ND9542P | H.265, 32CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI |
| 200 – NVR – Embedded | ND9326P | H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 2 LAN(Giga), 8 PoE, Core+ AI |
| 200 – NVR – Embedded | ND9426P | H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE, Core+ AI |
| 201 – NVR – Recording Server | NR9581-v2 | H.265, 32CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2 |
| 201 – NVR – Recording Server | NR9681-v2 | H.265, 64CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2 |
| 201 – NVR – Recording Server | NR9682-v2 | H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2 |
| 201 – NVR – Recording Server | NR9782-v2 | H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2 |
| 201 – NVR – Recording Server | NR9581-v3 | H.265, 32CH(expandable to 128CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 8 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro |
| 201 – NVR – Recording Server | NR9682-v3 | H.265, 64CH(expandable to 192CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro |
| 202 – NVR – CMS Station | NS9521 | H.265, 32CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 2 HDD, 2 LAN(Giga), VAST2 Station |
| 203 – NVR – Mobile NVR | NV9321P | H.265, 8CH, 1 HDMI+1 VGA, 1080P @360 fps (12-CH) or 3840x2160 @90 fps (3-CH), swappable Dual SSD, RAID 0/1, 802.3at/af compliant PoE ports x 8 (M12) |
| 203 – NVR – Mobile NVR | NV9421P | H.265, 16CH, 1 HDMI+1 VGA, 1080P @360 fps (12-CH) or 3840x2160 @90 fps (3-CH), swappable Dual SSD, RAID 0/1, 802.3at/af compliant PoE ports x 8 (M12) |
| 310 – PoE – Unmanaged Switch | AW-FET-060C-065 | 4xFE POE +2FE UTP Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-100D-120 | 8xFE PoE + 2xGE Combo Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-180D-250 | 16xFE POE +2G COMBO Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-260D-380 | 24xFE POE +2G COMBO Switch |
| 310 – PoE – Unmanaged Switch | AW-GET-050A-065,USA | 4xGE POE + 1xGE SWITCH |
| 310 – PoE – Unmanaged Switch | AW-GET-100A-120,USA | 8XGE POE + 2XG SFP SWITCH |
| 310 – PoE – Unmanaged Switch | AW-FET-060D-065 | 4xFE PoE + 2xFE RJ45 Unmanaged Switch, Power Budget 65W |
| 310 – PoE – Unmanaged Switch | AW-FGT-180F-250 | 16xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 250W |
| 310 – PoE – Unmanaged Switch | AW-FGT-260F-380 | 24xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 380W |
| 310 – PoE – Unmanaged Switch | AW-FET-060P-060 | 4xFE PoE + 2xFE RJ45 Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-100P-110 | 8xFE PoE + 2xGbE Combo Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-180P-250 | 16xFE PoE + 2xGbE Combo Switch |
| 310 – PoE – Unmanaged Switch | AW-FGT-260P-370 | 24xFE PoE + 2xGbE Combo Switch |
| 311 – PoE – Managed Switch | AW-GEV-104B-130,USA | 8-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE O utput Power Max. 130W) Integrate with VIVOTEK Camera for surveillance application |
| 311 – PoE – Managed Switch | AW-GEV-107A-130,USA | 8-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 130W) Integrate with VIVOTEK Camera for surveillance application |
| 311 – PoE – Managed Switch | AW-GEV-184B-250,USA | 16-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 250W) Integrate with VIVOTEK Camera for surveillance application |

| | | |
|---------------------------------|---------------------|--|
| 311 – PoE – Managed Switch | AW-GEV-264B-370,USA | 24-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 370W) Integrate with VIVOTEK Camera for surveillance application |
| 311 – PoE – Managed Switch | AW-GEV-267A-370,USA | 24-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 370W) Integrate with Vivotek Camera for surveillance application |
| 311 – PoE – Managed Switch | AW-GTS-287A,USA | 24xGE SFP + 4xCombo GE + 4x 10G SFP+ L2 Plus Managed Switch |
| 311 – PoE – Managed Switch | AW-GEV-108A-130 | VIVOCAM L2 Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 2xGbE Combo + 1xRJ45 console port, Power Budget 130W |
| 311 – PoE – Managed Switch | AW-GEV-288A-370 | VIVOCAM L2 Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 4xGbE Combo + 1xRJ45 Console port, Power Budget 370W |
| 311 – PoE – Managed Switch | AW-GEL-065A-060 | Lite Managed PoE Switch 4xGbE PoE + 2xGbE RJ45, Power Budget 60W |
| 311 – PoE – Managed Switch | AW-GEL-105A-110 | Lite Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 1xGbE RJ45 + 1xGbE SFP, Power Budget 110W |
| 311 – PoE – Managed Switch | AW-GEL-205A-260 | Lite Managed PoE Switch 4xGbE bt 90W PoE + 12xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 260W |
| 311 – PoE – Managed Switch | AW-GEL-285A-380 | Lite Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 380W |
| 312 – PoE – Optical Transceiver | SFP-1000-CPTX-X1 | Gigabit SFP to RJ45 Module |
| 312 – PoE – Optical Transceiver | SFP-1000-CPTX-X1I | Industrial Gigabit SFP to RJ45 Module |
| 312 – PoE – Optical Transceiver | SFP-1000-MM13-02 | Gigabit Mini GBIC Multi Mode 1310nm 2KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-MM13-02I | Industrial Gigabit Mini GBIC Multi Mode 1312nm 2KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-MM85-X5 | Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-MM85-X5I | Industrial Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-SM13-10 | Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-SM13-10I | Industrial Gigabit Mini GBIC Single Mode 1312nm 10KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-SM13-40 | Gigabit Mini GBIC Single Mode 1310nm 40KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-1000-SM13-40I | Industrial Gigabit Mini GBIC Single Mode 1312nm 40KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-2000-MM85-X3 | 10 Gigabit Mini GBIC Multi Mode 850nm 0.3KM, LC Connector |
| 312 – PoE – Optical Transceiver | SFP-2000-SM13-10 | 10 Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector |
| 320 – PoE – Industrial | AW-IHH-0800 | Industrial 4xGE 95W PoH/PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 95W, Power budget 240W, 54~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-0800 | Industrial 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 120W, 48~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-1000 | Industrial 8xGE PoE + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 240W, 48~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-1271 | Industrial VivoCam L2+ Managed PoE Switch 8xGE PoE + 4xGE SFP Per PoE port Max. 30W, power budget 240W, 48~57VDC input, - 40° C to 75° C |
| 320 – PoE – Industrial | AW-IHH-0110 | Industrial Gigabit 95W POH/POE Injector Industrial Gigabit 95W POH Injector, 48- 56VDC input, -40° C to +75° C |
| 320 – PoE – Industrial | AW-IHS-0202 | Industrial Media Convert SFP True Mini Industrial Media Converter, 10/100M RJ45 to 100M SFP, Designed for outdoor CAM enclosure, Din-Rail mount and Panel mount, 18-36VAC/12- 60VDC, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-0100 | Industrial Gigabit 30W POE Injector Industrial Gigabit 30W POE Injector, 48-56VDC input, -40° C to +75° C |
| 320 – PoE – Industrial | AW-IHT-0200 | Industrial 1xGE PoE + 1xGE SFP Switch 1 port 802.3at 30W POE 10/100/1000M + 1 port 100/1000M SFP, 48~56VDC inp ut, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHH-0410 | Industrial 2xGE 95W POH/POE + 2xGE SFP Switch, 48~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-0601 | Industrial 4XGE POE+2XGE SWITCH SFP 12V-56V Super Voltage Booster 12~56VDC input, 4 port 802.3at 30W POE 10/100/1000M + 1 port 10/100/1000M SFP/TX Combo + 1 port 100/1000M SFP, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-0602 | Industrial EN50155 4xFE M12 PoE + 2xFE M12 Switch 4 port 802.3at 30W POE M12 10/100M + 1 port M12 10/100M, 24~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHB-0100 | Industrial Gigabit 802.3bt 90W PoE injector, 48-56VDC input, -40° C to +75° C |
| 320 – PoE – Industrial | AW-IHB-0400 | Industrial 2xGE 802.3bt 90W PoE + 2xGE SFP Switch, power budget 180W, 48~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHB-0800 | Industrial 4xGE 802.3bt 90W PoE + 2xGE UTP + 2xGE SFP Switch, power budget 360W, 54~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHB-1040 | Industrial Lite Managed PoE Switch 2xGbE bt 90W + 6xGbE af/at 30W + 2xGbE SFP, Power budget 300W, 48~56VDC input, -40° C to 75° C |
| 320 – PoE – Industrial | AW-IHT-1002 | Industrial M12 PoE Switch 8xFE D-coded PoE + 2xGbE X-coded, EN50155/EN45545-2, -40° C to 75° C |
| 321 – PoE – Extender | AP-FXC-0110 | 1-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C |
| 321 – PoE – Extender | AP-FXC-0160 | 1-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C |
| 321 – PoE – Extender | AP-FXC-0210 | 2-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C |
| 321 – PoE – Extender | AP-FXC-0260 | 2-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C |
| 321 – PoE – Extender | AP-GXC-0150 | 1-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C |

| | | |
|--------------------------|---------------------|---|
| 321 – PoE – Extender | AP-GXC-0250 | 2-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C |
| 321 – PoE – Extender | AP-GXC-0100 | 1-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C |
| 321 – PoE – Extender | AP-GXC-0200 | 2-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C |
| 321 – PoE – Extender | AP-FXC-0400 | 4-Port indoor FE PoE Extender |
| 321 – PoE – Extender | AP-FHP-0100-R | Hyper PoE PoE in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C |
| 321 – PoE – Extender | AP-FHP-0105-R,USA | Hyper PoE DC in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C AA- 420, US power cord |
| 321 – PoE – Extender | AP-FHP-0105-T | Hyper PoE Tx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C |
| 322 – PoE – Injector | AP-FIC-010A-015,USA | Indoor IEEE802.3af FE PoE Injector |
| 322 – PoE – Injector | AP-GIC-010A-030,USA | Indoor IEEE802.3at Gigabit PoE Injector |
| 322 – PoE – Injector | AP-GIC-011A-060,USA | Indoor Gigabit PoH 60W Injector |
| 322 – PoE – Injector | AP-GIC-011A-095,USA | Indoor Gigabit PoH 95W Injector |
| 322 – PoE – Injector | AP-GIC-015B-095 | outdoor Gigabit PoH 95W Injector |
| 322 – PoE – Injector | AP-GIC-011A-030 | Indoor Gigabit IEEE 802.3at 30W PoE Injector |
| 322 – PoE – Injector | AP-GIC-011B-090 | Indoor Gigabit IEEE 802.3bt 90W PoE Injector |
| 330 – PoE – Cabinet | AT-CAB-001 | Cabinet IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory device s such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover is included. |
| 330 – PoE – Cabinet | AT-CAB-002 | Side-mount bracket for HLG series power supply Protects accessory devices such as 120W power supply. |
| 330 – PoE – Cabinet | AT-CAS-001 | Cabinet for Speed dome IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory device s such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover |
| 330 – PoE – Cabinet | AT-DRB-001 | Cabinet industrial 95W PoE switch AW-IHH-0800 bracket |
| 330 – PoE – Cabinet | AT-PSP-001 | PoE Surge Protector: 8-10KA AT-PSP-001 is a surge protection device to provide Signal/Power path and surge protection capability. It employed our patented surge blocker wit h shunt devices and parallel devices to guarantee the safety of your dev ice, ev |
| 330 – PoE – Cabinet | AT-SUN-001 | Sunshield for AT-CAx series cabinet Metal sunshield for Vivotek Cabinet series. Reduces the temperature insi de the cabinet, caused by sun radiation. |
| 330 – PoE – Cabinet | AT-SUN-002 | Sunshield for AT-CAx + AT-CAB-002 cabinet Metal sunshield for BOTH Vivotek Cabinet and DC Power cabinet. Reduces the temperature inside the cabinet, caused by sun radiation. |
| 330 – PoE – Cabinet | AT-SWH-000 | Power Safety Kit (100~275VAC): 20-40KA Electrical safety kit for Vivotek Cabinet in countries where the mains p ower is 275V AC. Included products: Surge protector class 2, Fuse/main switch, terminal b locks and an intrusion door switch. |
| 330 – PoE – Cabinet | AT-SWH-002 | Door open/close detection switch Intrusion door switch for Vivotek Cabinet, connection to I/O port. |
| 330 – PoE – Cabinet | AT-WPC-001 | Cable gland M16 CABLE GLAND 4~7mm AWG 6PCS |
| 330 – PoE – Cabinet | AT-WPC-002 | Cable gland M16 CABLE GLAND for Corrugated Tubing : 5/16 " 6PCS |
| 330 – PoE – Cabinet | AP-PSP-050 | Outdoor PoE Surge Protector 16KV surge Operating temperature from -40° C to 85 ° C |
| 330 – PoE – Cabinet | AW-GEH-043A-120 | Outdoor Unmanaged 2xGE 95W PoH/PoE + 2xGE SFP Switch, Per PoE port max. 95W, power budget 120W, IP67, IK10 |
| 330 – PoE – Cabinet | AW-GET-083A-120 | Outdoor Unmanaged 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port max. 30W, power budget 120W, IP67, IK10 |
| 330 – PoE – Cabinet | AW-GEU-086A-240 | Outdoor VivoCam L2+ Managed 4xGE UPoE + 2xGE UTP + 2xGE SFP Switch, Per PoE Port max. 60W, power budget 240W, IP67, IK10 |
| 331 – PoE – Power Supply | HLG-120H-24 | 90~305VAC In ,24VDC/120Wut ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-120H-48 | 90~305VAC In ,48VDC/120W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-120H-54 | 90~305VAC In ,54VDC/120W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-240H-54 | 90~305VAC In ,54VDC/240W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-60H-24 | 90~305VAC In ,24VDC/60Wut ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-80H-24 | 90~305VAC In ,24VDC/80W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-80H-48 | 90~305VAC In ,48VDC/80W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | HLG-80H-54 | 90~305VAC In ,54VDC/80W Out ,IP67, - 40 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | NDR-120-48 | 90~264VAC In, 48VDC/120W Out , - 20 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | NDR-240-48 | 90~264VAC In, 48VDC/240W Out , - 20 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | NDR-75-48 | 90~264VAC In, 48VDC/75W Out , - 20 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | DRL-48V120W1EN | 90~264VAC In, 48VDC/120W Out , - 30 ° C ~ 70 ° C |
| 331 – PoE – Power Supply | DRL-48V240W1EN | 90~264VAC In, 48VDC/240W Out , - 30 ° C ~ 70 ° C |
| 340 – PoE – EPoC | AM-713-E_V01 | Conduit box with EPoC Tx module for Outdoor fixed dome |
| 340 – PoE – EPoC | AP-FEX-0100-R | EPoC PoE in Rx Module, 1x BNC, 1x FE RJ45, -20 ° C~60 ° C |
| 340 – PoE – EPoC | AP-FEX-0105-D,USA | EPoC Extender DC kit, AP-FEX-0105-R + AP-FEX-0105-T + AA-420, USA |
| 340 – PoE – EPoC | AP-FEX-0105-P | EPoC Extender PoE kit, AP-FEX-0100-R + AP-FEX-0105-T |
| 340 – PoE – EPoC | AP-FEX-0105-R,USA | EPoC DC in Rx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C, AA-420, USA |

| | | |
|-----------------------------|---------------------|---|
| 340 – PoE – EPoC | AP-FEX-0105-T | EPoC DC in Tx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C |
| 340 – PoE – EPoC | AP-FEX-0150-T | EPoC Outdoor Tx Module, 1x BNC, 1x FE RJ45, -40 ° C~60 ° C, IP67, IK10 |
| 340 – PoE – EPoC | AP-FEX-0200-T | EPoC Tx Module, 1x BNC, 2x FE RJ45, -20 ° C~60 ° C |
| 340 – PoE – EPoC | AP-FEX-0250-T | EPoC Outdoor Tx Module, 1x BNC, 2x FE RJ45, -40 ° C~60 ° C, IP67, IK10 |
| 340 – PoE – EPoC | AT-BSP-001 | Coax surge protector for EPoC modules |
| 340 – PoE – EPoC | AW-FCT-050A-250,USA | 4xFE BNC + 1x GE RJ45 unmanaged EPoC switch, USA |
| 410 – Accessory – Enclosure | AE-238 | Side Open Aluminum Camera Housing AC24V in, Window heater, Fan, IP68, -20~50°C , wall bracket&sun shield |
| 410 – Accessory – Enclosure | AE-239 | Side Open Aluminum Camera Housing PoE in, Window heater, Fan, IP68, -20~50°C, wall bracket&sun shield |
| 410 – Accessory – Enclosure | AE-243 | Side Open Aluminum Camera Housing, AC24V in, Window heater, Fan, IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield |
| 410 – Accessory – Enclosure | AE-244 | Side Open Aluminum Camera Housing, PoE in, Window heater, Fan, IP68, -20~50°C, 6W fixed IR, Wall Bracket, Sun shield |
| 410 – Accessory – Enclosure | AE-23A | Side Open Aluminum Camera Housing AC24V in, Window heater, Fan, IP68, -20~50°C , optional snap-in VAIR, Wall bracket, Sun shield |
| 410 – Accessory – Enclosure | AE-23E-v2 | Side Open Aluminum Camera Housing, PoE in (BT), Window heater, Fan, IP68, |
| 411 – Accessory – CaMate | CA80I8-1040 | IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w |
| 411 – Accessory – CaMate | CA80I8-2040 | IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w |
| 411 – Accessory – CaMate | CM32I8-010 | IR illuminator fixed IR 10°, 180m, 32w |
| 411 – Accessory – CaMate | CM32I8-035 | IR illuminator fixed IR 35°, 60m, 32w |
| 411 – Accessory – CaMate | CM48I8-1040 | IR illuminator with CVA, 10°~ 40°, 100~250m, 48w |
| 411 – Accessory – CaMate | CM48I8-180 | IR illuminator with CVA, 180°, 40m, 48w |
| 411 – Accessory – CaMate | CM48I8-2040 | IR illuminator with CVA, 20°~ 40°, 120 ~ 200m, 48w |
| 411 – Accessory – CaMate | CM48I8-4080 | IR illuminator with CVA, 40°~ 80°, 60~90m, 48w |
| 411 – Accessory – CaMate | CM48I8-90120 | IR illuminator with CVA, 90°~ 120°, 45~55m, 48w |
| 501 – Facial Recognition | FT9361-R | Facial Recognition Access Control Tablet, Linux OS, Memory: 8GB ROM 1GB RAM, Max. 50,000 profiles, 1080P camera, 1440x720 display, PoE Class 4/DC 12V, Weigand |
| 501 – Facial Recognition | IE9281-FM | Content Management System Support up to 256 Devices in One Single Server Support of Local Display via HDMI Easy to Integrate into Your System Rich Infographic Reports <u>Support Rackmount Installation</u> |
| 501 – Facial Recognition | IE9232-F | Mask Detection and Recognition Enroll a Person's Profile with up to 5 Pictures Real-time Notifications and Alerts Persons of Interest (POI) Management Comprehensive Reports Support up to 6 Cameras/Servers |