



**V Series**

# ND9541

H.265 32-CH Embedded NVR



## Technical Specifications

Technical Specifications	
Descriptions	32-CH Embedded NVR

Device	
OS	Embedded Linux
Watchdog	Hardware + Software
Power Restoration	System Restart Automatically after Power Recovery

Display	
LiveView Display	32 Channels Multi Layout display: 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4, 1M+31
Video Output	HDMI x1, VGA x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant/Auto Adaptive Stream
Fisheye Dewarp	10, 1P, 1R, 1O3R, 1O8R
PTZ Operation	Direction Control, Home, Iris, Preset, Patrol (Group), PiP Control

Video	
Video Format	MJPEG, H.264, H.265
Graphic Decoder	Hardware decoding
Decoding Resolution	Up to 7680x2560
Decoding Capability	H.265/H.264: 3840x2160 @ 120 fps 1920x1080 @ 480 fps

## Audio

Audio Format	G.711, G.726
--------------	--------------

## Record

Recording Time (sec.)	Pre-Record: 5 (Max. 10) Post-Record: 20 (Max. 300)
Recording Stream	Single
Recording Throughput	192 Mbps
Recording Mode	Continuous, Schedule, Manual, Event, Activity Adaptive Streaming
Recording Setting	Recycle (unit: Day)
Watermark	Supported

## Storage & Backup

DISK Devices	Internal x4 (3.5") (HDD is purchased by separately)
HDD Max. Capacity	Please refer to HDD supported list on VIVOTEK website
RAID	RAID 0, 1, 5 (single volume up to 16TB)
Disk Management	Create, Format and Remove Disk HDD S.M.A.R.T
External Storage	USB Storage (USB 3.0)
Video Clip Export	USB pen drive (FAT Format)
Schedule Backup	FTP

## Playback

Playback Display	4 Channels Multi Layout Display: 1x1,2x2,1P+3,1V+3
Playback Control	Regular (Play, Pause, Stop), Rewind, Next / Previous Frame, Speed Control, Calendar, Event, Timeline, Timeline Scale, Thumbnail (Storyboard)
Video Search	By Calendar, Date/Time, and Alarm
Thumbnail Explorer (Storyboard)	Listing the thumbnail of recorded video (Max. 2 CH)
Snapshot	JPEG
Video Clip Export	EXE

## Network

Ethernet	10/100/1000Mbps Ethernet (RJ-45) x 2
Network Throughput in total	96 Mbps
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS

## External Interface

USB	Front: 2 (USB 2.0) Back: 1 (USB 3.0)
Alarm In	8
Alarm Out	4
Audio In	3.5 Phone Jack Audio Input x1 (HW available, FW feature not supported yet)

RS485	1 ( (HW available, FW feature not supported yet)
-------	--

## System

Camera Integration	ONVIF Profile S
Event	Motion Detection, Smart VCA Event, Cyber Attack, PIR Detection, Tampering Detection, Camera DI/DO, Camera Disconnected, Disk Failure, Disk Full, NVR DI/DO, PoE error
Event Action	Record, Email (Text), Email (Snapshot), FTP, Buzzer, ePTZ Control (Go to Preset), NVR DO, Camera DO, VIVOCLOUD APP Notification
User Management	User level: administrator, regular user
Log	System, Recording, User, Error
Date&Time	Time Zone, Manual, Automatic Sync NTP, Daylight Saving Time
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese, Arabic

## Advance Features

VCA Counting Solution	Supported
VCA Event Search	Smart VCA, Smart 360 VCA
Smart Search II	Supported
Trend Micro IoT Security	Supported (3-year free trial)
Cybersecurity Management	Supported

## Remote Client

Software AP	Shepherd , VSS
Mobile/Tablet App	iViewer (Android & iOS)
Web Browser	Chrome
Cloud service	VIVOCLOUD

## General

Power Input	DC 56V 1.34A
Power Consumption	Max. 76 W
Dimensions	430 (W) x 400 (D) x 44.5 (H) mm
Weight	3.87 kg (without HDD)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0 ~ 95%
Safety Certifications	CE, LVD, FCC, VCCI, C-Tick , UL

