



AP-GXC-0150

Outdoor 1-Port GE PoE Extender



Technical Specifications

Extension Distance	2 Units, Daisy-chain Installation Up to 300M Extension (No Local Power Required)
PoE Input Power	802.3 af/at/bt & PoH up to 95W
PoE output Power	48~55VDC, max. 68W Passive PoE
PD Power Pin Assignment	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)
PSE Power Pin Assignment	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)
PD Gigabit Ethernet (RJ45)	1
PSE Gigabit Ethernet (RJ45)	1
PSE Power On/Off Dip Switch	Supported
Surge Protection /PoE Port	6KV
Total Gigabit Ethernet Port	2
Mac Table	2K
Bandwidth	10/100/1000 Mbps
Switching Capacity	4 Gbps
Auto-MDI/MDI-X, Auto-Negotiation	Supported
Dimensions (WxHxD)	157 x 55.8 x 39.75 mm
Weight	0.3 KG
LED Indicators	Power, LAN, PoE
Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Operating Humidity	10% to 90% non-condensing
Waterproof	IP67
Vandal Proof	IK10
EMC	CE,FCC,VCCI,C-Tick