



S Series

NV9411P

H.265 16-CH Embedded PoE
Mobile NVR



技術規格

技術規格

說明	16-CH Embedded PoE Mobile NVR
----	-------------------------------

裝置

作業系統	Embedded Linux
看門狗	Hardware + Software
電源恢復	System Restart Automatically after Power Recovery

顯示

即時影像顯示	16 Channels Multi-layout display: 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4
影像輸出	HDMI x1, VGA x1
顯示解析度	3840x2160, 1920x1080, 1280x720
串流應用情境	Constant\Auto Adaptive Stream
魚眼矯正	10, 1P, 1R, 1O3R, 1O8R
PTZ 操作	Direction Control, Home, Iris, Preset, Patrol (Group)

影像

影像格式	MJPEG, H.264, H.265
圖形解碼器	Hardware decoding
解碼解析度	UP to 3840x2160
解碼能力	3840x2160 @ 120 fps (4-CH) 1920x1080 @ 240 fps (8-CH) 1920x1080 @ 480 fps (16-CH)

音訊

音訊格式	G.711, G.726
音訊輸入/輸出	Line out x 1

錄影

錄影時間 (秒)	Pre-Record: 5 (Max. 10) Post-Record: 20 (Max. 300)
錄影串流	Single
錄影處理量	64 Mbps
錄影模式	Continuous, Schedule, Manual, Event, Activity Adaptive Streaming
錄影設定	Recycle (unit: Day)
浮水印	Supported

儲存與備份

磁碟裝置	Internal x1 (2.5" HDD/SSD) (HDD is purchased by separately)
硬碟最大容量	Please refer to HDD supported list on VIVOTEK website
磁碟管理	Create, Format and Remove Disk HDD S.M.A.R.T
SD 卡	SD card slot x1 (reserved)
影像剪輯匯出	USB Dongle (FAT Format)
排程備份	FTP

觀看錄影

播放顯示	4 Channels Multi Layout Display: 1x1,2x2,1P+3,1V+3
播放控制	Regular (Play, Pause, Stop), Rewind, Next / Previous Frame, Speed Control, Calendar, Event, Timeline, Timeline Scale, Thumbnail (Storyboard)
影片搜尋	By Calendar, Date/Time, and Alarm
縮圖瀏覽 (分鏡)	Listing the thumbnail of recorded video (Max. 2 CH)
擷圖	JPEG
影像剪輯匯出	EXE

網路

乙太網路	10/100/1000Mbps Ethernet (RJ-45) x 1
總網路處理量	96 Mbps
WiFi	802.11a/b/g/n/ac 2T2R (optional)
行動網路	LTE (optional)
PoE	802.3at/af compliant PoE ports x 8 (RJ45) (Total Max. 64W)
PoE 管理	Supported
通訊協定	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

外部介面

USB	Front x2 (USB 2.0) Back x1 (USB 2.0)
警報輸入	8
警報輸出	4
音訊	Line out x 1
天線介面	GPS x1, WiFi x2, LTE x2
RS232	1 Port (Reserved)

系統

攝影機整合	ONVIF Profile S
GNSS	GPS/GALILEO/GLONASS supported
重力感測器	Supported
事件	Motion Detection, PIR Detection, Tampering Detection, Camera DI/DO, Camera Disconnected, Disk Failure, Disk Full, NVR DI/DO, GPS disconnected, GPS speed, G-sensor
事件動作	Video recording, email with snapshot, buzzer, PTZ, FTP, DO (camera, system), full screen, send to CMS
使用者管理	User level: administrator, regular user
記錄	System, Recording, User, Error
日期與時間	Time Zone, Manual, Automatic Sync NTP, Daylight Saving Time
語言	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

遠端用戶端

軟體 AP	Shepherd ,VAST 2
手機/平板電腦應用程式	iViewer (Android & iOS)
網頁瀏覽器	Internet Explorer 10 (32 bit) or later/ Windows Chrome v68.0.3 & Firefox v61.02 or later/ Windows & macOS

一般

電源輸入	DC 12V~48V \pm 10%
電源管理	Programmable delay on/off relative to ignition or other switched voltage
耗電量	Max. 149 W Without HDD/SSD and PoE: Max. 15 W (Heater off), Max. 60 W (Heater on)
尺寸	284 (W) x 230 (D) x 90 (H) mm
重量	4.06 kg (without HDD)
操作溫度	-40°C ~ 55°C (-40°F ~ 131°F)
濕度	0 ~ 95%
安全認證	CE, FCC, VCCI, C-Tick, EN50155, EN61373, UL, CB, EN45545, EN50121-3-2/EN50121-4, MIL-STD-810G