



RX9401

H.265 16-CH Embedded Video Receiver



技術仕様

Technical Specifications

Descriptions	16-CH Embedded Video Decoder
--------------	------------------------------

Device

OS	Embedded Linux
Watchdog	ハードウェア + ソフトウェア
Power Restoration	電源復旧後システムは自動的に再起動

Display

LiveView Display	16 チャンネル マルチレイアウトディスプレイ : 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4
Video Output	HDMI x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant ¥ Auto Adaptive Stream
Fisheye Dewarp	10, 1P, 1R, 103R, 108R
PTZ Operation	方向コントロール、ホーム、プリセット、パトロール (グループ)

Video

Video Format	H.264, H.265
Graphic Decoder	ハードウェア デコード
Decoding Resolution	最大 3840x2160
Decoding Capability	3840x2160 @ 30 fps (1CH) 1920x1080 @ 120 fps (4CH) 720x480 @ 480fps (16CH)

Audio

Audio Format	G.711, G.726
--------------	--------------

Network	
Ethernet	10/100Mbps Ethernet (RJ-45) x 1
Network Throughput in total	40 Mbps
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

External Interface	
USB	前面: 1 (USB 2.0) 背面: 1 (USB 2.0)

System	
Camera Integration	ONVIF core spec 2.2 or above (*by project)
User Management	ユーザーレベル: 管理者、レギュラー ユーザー
Date&Time	タイムゾーン、手動、自動同期NTP、夏時間
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

Remote Client	
Software AP	Shepherd ,VAST 2(reserved)
Web Browser	Internet Explorer 10 (32 bit) or above

General	
Power Input	DC 12V 1.5A
Power Consumption	Max. 9.24 W
Dimensions	198 (W) x 200 (D) x 47(H)mm
Weight	530 g
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick