



# RX9401

## H.265 16-CH Embedded Video Receiver



### Especificaciones Técnicas

Technical Specifications	
Descriptions	16-CH Embedded Video Decoder
Device	
OS	Embedded Linux
Watchdog	Hardware + Software
Power Restoration	Reinicio automático del sistema después de la recuperación de energía
Display	
LiveView Display	16 canales Visualización de diseño múltiple: 1x1, 2x2, 3x3, 1P+3,2P+3,1M+5, 1P+6, 3V,1M+12, 4x4
Video Output	HDMI x1
Display Resolution	3840x2160,1920x1080, 1280x720
Stream Application	Constant\Auto Adaptive Stream
Fisheye Dewarp	10,1P,1R,1O3R,1O8R
PTZ Operation	Control de dirección, Inicio, Enfoque, Preestablecido, Patrulla (Grupo)
Video	
Video Format	H.264, H.265
Graphic Decoder	Decodificación de hardware
Decoding Resolution	Hasta 3840x2160
Decoding Capability	3840x2160 @ 30 fps (1CH) 1920x1080 @ 120 fps (4CH) 720x480 @ 480fps (16CH)
Audio	
Audio Format	G.711, G.726

Network	
Ethernet	10/100Mbps Ethernet (RJ-45) x 1
Network Throughput in total	40 Mbps
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

External Interface	
USB	Frontal: 1 (USB 2.0) Trasera: 1 (USB 2.0)

System	
Camera Integration	ONVIF core spec 2.2 or above (*by project)
User Management	Nivel de usuario: administrador, usuario regular
Date&Time	Zona horaria, Manual, Sincronización automática NTP, Horario de verano
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

Remote Client	
Software AP	Shepherd ,VAST 2(reserved)
Web Browser	Internet Explorer 10 (32 bit) or above

General	
Power Input	DC 12V 1.5A
Power Consumption	Max. 9.24 W
Dimensions	198 (W) x 200 (D) x 47(H)mm
Weight	530 g
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick