



# AU-002



## Technical Specifications

### Product Information

Rated Impedance	Lower to 3 ohm speaker totally(Driver)
Max. Power Consumption	20 W
Microphone	100Hz-16KHz Single point, SPL-44 ± 2db AT 2 KΩ

### Network

SIP Support	RFC 3261(SIP base standard)
Interface	WAN: RJ-45x1, 10/100Mbps Fast Ethernet port
Supported Protocols	SIP, IPv4/v6, RIPv2 / OSPF, HTTPS, QoS DSCP, FTP, TFTP, SNMP v2c / v3, SNMP, IGMP, DHCP, SSHv2, PIM- DVMRP, RMON
Audio Codec	G.711 a/uLaw, G.726, G.722, G.729, iLBC, L16
Support Function	Auto provision, Audio tone testing, System log
Security	Password protection, IP address filter, user access log, authentication

### VSS Integration

Broadcasting	Supported
Automatic Trigger Audio Clips	Supported

### General

Casing	Plastic
Power	PoE+ (Power over Ethernet), IEEE 802.3at
Operating Temperature	-35°C ~ 60°C (-31°F ~ 140°F)
Dimensions	110 x 85 x 25 mm
Weight	115 g
Certifications	CE, FCC, LVD EN62368-1

LED Luminous	3x LED display status
Material	Plastic