



RX9502

H.265 32-CH Embedded Video Receiver



Especificaciones Técnicas

Technical Specifications

Descriptions	32-CH Embedded Video Decoder
--------------	------------------------------

Device

OS	Embedded Linux
Watchdog	Hardware + Software
Power Restoration	Reinicio automático del sistema después de la recuperación de energía

Display

LiveView Display	32 canales Visualización de diseño múltiple: 1x1, 2x2, 3x3, 4x4, 1M+5, 1M+12, 1M+31, 1P+3, 1P+6, 2P+3, 3V
Video Output	HDMI x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant\Auto Adaptive Stream
Fisheye Dewarp	10, 1P, 1R, 1O3R, 1O8R, 1P3R
PTZ Operation	Control de dirección, Inicio, Enfoque, Preestablecido, Patrulla (Grupo)

Video

Video Format	H.264, H.265, MJPEG
Graphic Decoder	Decodificación de hardware
Decoding Resolution	Hasta 7680x2560
Decoding Capability	3840x2160 @ 90 fps (3C-H) 1920x1080 @ 360 fps (12-CH)

Audio

Audio Format	G.711, G.726
--------------	--------------

Network

Ethernet	10/100/1000Mbps Ethernet (RJ-45) x 1
Network Throughput in total	192 Mbps
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS

External Interface

USB	Frontal: 1 (USB 2.0) Trasera: 1 (USB 3.0)
-----	--

System

Camera Integration	ONVIF Profile S
User Management	Nivel de usuario: administrador, usuario regular
Date&Time	Zona horaria, Manual, Sincronización automática NTP, Horario de verano
Language	Checo, Inglés, Francés, Alemán, Italiano, Japonés, Coreano, Portugués, Polaco, Ruso, Español, Chino simplificado, Chino tradicional, Árabe

Remote Client

Software AP	Shepherd ,VAST 2, VSS
Web Browser	Chrome

General

Power Input	DC 12V 1A
Power Consumption	Max. 11W
Dimensions	198 (W) x 200 (D) x 47(H)mm
Weight	530 g
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick ,UL, CB, BSMI, BIS