



S Series

NV9411P

H.265 16-CH Embedded PoE Mobile NVR



Technical Specifications

Technical Specifications	
Descriptions	16-CH Embedded PoE Mobile NVR
Device	
OS	Embedded Linux
Watchdog	Hardware + Software
Power Restoration	System Restart Automatically after Power Recovery
Display	
LiveView Display	16 Channels Multi-layout display: 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4
Video Output	HDMI x1, VGA x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant\Auto Adaptive Stream
Fisheye Dewarp	10,1P,1R,103R,108R
PTZ Operation	Direction Control, Home, Iris, Preset, Patrol (Group)
Video	
Video Format	MJPEG, H.264, H.265
Graphic Decoder	Hardware decoding
Decoding Resolution	UP to 3840x2160
Decoding Capability	3840x2160 @ 120 fps (4-CH) 1920x1080 @ 240 fps (8-CH) 1920x1080 @ 480 fps (16-CH)

Audio

Audio Format	G.711, G.726
Audio In/Out	Line out x 1

Record

Recording Time (sec.)	Pre-Record: 5 (Max. 10) Post-Record: 20 (Max. 300)
Recording Stream	Single
Recording Throughput	64 Mbps
Recording Mode	Continuous, Schedule, Manual, Event, Activity Adaptive Streaming
Recording Setting	Recycle (unit: Day)
Watermark	Supported

Storage & Backup

DISK Devices	Internal x1 (2.5" HDD/SSD) (HDD is purchased by separately)
HDD Max. Capacity	Please refer to HDD supported list on VIVOTEK website
Disk Management	Create, Format and Remove Disk HDD S.M.A.R.T
SD Card	SD card slot x1 (reserved)
Video Clip Export	USB Dongle (FAT Format)
Schedule Backup	FTP

Playback

Playback Display	4 Channels Multi Layout Display: 1x1,2x2,1P+3,1V+3
Playback Control	Regular (Play, Pause, Stop), Rewind, Next / Previous Frame, Speed Control, Calendar, Event, Timeline, Timeline Scale, Thumbnail (Storyboard)
Video Search	By Calendar, Date/Time, and Alarm
Thumbnail Explorer (Storyboard)	Listing the thumbnail of recorded video (Max. 2 CH)
Snapshot	JPEG
Video Clip Export	EXE

Network

Ethernet	10/100/1000Mbps Ethernet (RJ-45) x 1
Network Throughput in total	96 Mbps
WiFi	802.11a/b/g/n/ac 2T2R (optional)
Mobile Network	LTE (optional)
PoE	802.3at/af compliant PoE ports x 8 (RJ45) (Total Max. 64W)
PoE Management	Supported
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

External Interface	
USB	Front x2 (USB 2.0) Back x1 (USB 2.0)
Alarm In	8
Alarm Out	4
Audio	Line out x 1
Antenna Interface	GPS x1, WiFi x2, LTE x2
RS232	1 Port (Reserved)

System	
Camera Integration	ONVIF Profile S
GNSS	GPS/GALILEO/GLONASS supported
G-sensor	Supported
Event	Motion Detection, PIR Detection, Tampering Detection, Camera DI/DO, Camera Disconnected, Disk Failure, Disk Full, NVR DI/DO, GPS disconnected, GPS speed, G-sensor
Event Action	Video recording, email with snapshot, buzzer, PTZ, FTP, DO (camera, system), full screen, send to CMS
User Management	User level: administrator, regular user
Log	System, Recording, User, Error
Date&Time	Time Zone, Manual, Automatic Sync NTP, Daylight Saving Time
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

Remote Client	
Software AP	Shepherd ,VAST 2
Mobile/Tablet App	iViewer (Android & iOS)
Web Browser	Internet Explorer 10 (32 bit) or later/ Windows Chrome v68.0.3 & Firefox v61.0.2 or later/ Windows & macOS

General	
Power Input	DC 12V~48V ±10%
Power Management	Programmable delay on/off relative to ignition or other switched voltage
Power Consumption	Max. 149 W Without HDD/SSD and PoE: Max. 15 W (Heater off), Max. 60 W (Heater on)
Dimensions	284 (W) x 230 (D) x 90 (H) mm
Weight	4.06 kg (without HDD)
Operating Temperature	-40°C ~ 55°C (-40°F ~ 131°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick, EN50155, EN61373, UL, CB, EN45545, EN50121-3-2/EN50121-4, MIL-STD-810G