



AW-GET-083A-120

4xGE PoE + 2GE UTP + 2xGE SFP



Technical Specifications

Product Information

Segment	Unmanaged PoE Switch
Product Description	4xGE PoE + 2GE UTP + 2xGE SFP Outdoor PoE Switch

Port Configuration

PoE Port Ethernet	4xGbE PoE
Uplink Port Ethernet	2xGbE RJ45 + 2xGbE SFP
Total Ports	8

PoE Function

PoE Port	4
Max. PoE Output Power	30W
PoE Power Budget	120W
PoE Standard	802.3 af/at
PoE Pin Assignment	1/2 (+), 3/6 (-)
Surge Protection	6KV

HW Performance

Switching Bandwidth	16G
Buffer Memory	1.5Mb
Forwarding Rate	11.904 Mpps
MAC Address	8K
Jumbo Frames	9216 Bytes
Max. Power Consumption	130W

Environmental Specifications

Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	10 ~ 90% (Non-condensing)
Waterproof	IP67
Vandal Proof	IK10

Mechanical Specifications

Dimensions	315.4 (W) x 245.8 (H) x 118 (D) mm
Weight	4.52 kg

Power Source

Power Input	100V ~ 240V
Frequency	50 ~ 60 Hz

Certifications

Types	CB, CE,FCC,LVD,VCCI
-------	---------------------

Included Accessories

Content	QIG, Cable Gland
---------	------------------