

## FCC Test Report

**Report No.:** FD190124D02

**Test Model:** FD9380-HNWL

**Series Model:** FD9380-H

**Received Date:** Jan. 24, 2019

**Test Date:** Jan. 30 ~ 31, 2019

**Issued Date:** Feb. 25, 2019

**Applicant:** VIVOTEK INC.

**Address:** 6F, No.192, Lien-Cheng Rd., Chung-Ho , New Taipei City, 235, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**FCC Registration /  
Designation Number:** 418586 / TW1078



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Summary of Test Results</b> .....	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Modification Record .....	5
<b>3 General Information</b> .....	<b>6</b>
3.1 Description of EUT .....	6
3.2 Features of EUT .....	6
3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode .....	7
3.4 Test Program Used and Operation Descriptions.....	7
3.5 Primary Clock Frequencies of Internal Source .....	7
<b>4 Configuration and Connections with EUT</b> .....	<b>8</b>
4.1 Connection Diagram of EUT and Peripheral Devices.....	8
4.2 Configuration of Peripheral Devices and Cable Connections.....	10
<b>5 Conducted Emissions at Mains Ports</b> .....	<b>11</b>
5.1 Limits .....	11
5.2 Test Instruments .....	11
5.3 Test Arrangement.....	12
5.4 Test Results.....	13
<b>6 Radiated Emissions up to 1 GHz</b> .....	<b>17</b>
6.1 Limits .....	17
6.2 Test Instruments .....	17
6.3 Test Arrangement.....	18
6.4 Test Results.....	19
<b>7 Radiated Emissions above 1 GHz</b> .....	<b>23</b>
7.1 Limits .....	23
7.2 Test Instruments .....	24
7.3 Test Arrangement.....	25
7.4 Test Results.....	26
<b>8 Pictures of Test Arrangements</b> .....	<b>30</b>
8.1 Conducted Emissions at Mains Ports .....	30
8.2 Radiated Emissions up to 1 GHz .....	32
8.3 Radiated Emissions above 1 GHz .....	34
<b>Appendix – Information of the Testing Laboratories</b> .....	<b>36</b>

### Release Control Record

Issue No.	Description	Date Issued
FD190124D02	Original release.	Feb. 25, 2019

## 1 Certificate of Conformity

**Product:** Network Camera  
**Brand:** VIVOTEK  
**Test Model:** FD9380-HNWL  
**Series Model:** FD9380-H  
**Sample Status:** Engineering sample  
**Applicant:** VIVOTEK INC.  
**Test Date:** Jan. 30 ~ 31, 2019  
**Standards:** 47 CFR FCC Part 15, Subpart B, Class B  
ICES-003:2016 Issue 6, Class B  
ANSI C63.4:2014

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Albee Chu , **Date:** Feb. 25, 2019  
Albee Chu / Specialist

**Approved by :** Jim Hsiang , **Date:** Feb. 25, 2019  
Jim Hsiang / Associate Technical Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart B / ICES-003:2016 Issue 6, Class B

ANSI C63.4:2014

FCC Clause	ICES-003 Clause	Test Item	Result/Remarks	Verdict
15.107	6.1	Conducted Emissions at mains ports	Minimum passing Class B margin is -5.77 dB at 24.41797 MHz	Pass
15.109	6.2.1	Radiated Emissions up to 1 GHz	Minimum passing Class B margin is -3.07 dB at 168.00 MHz	Pass
	6.2.2	Radiated Emissions above 1 GHz	Minimum passing Class B margin is -14.76 dB at 1250.13 MHz	Pass

Note:

1. There is no deviation to the applied test methods and requirements covered by the scope of this report.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.79 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	3.97 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	4.77 dB
	Above 6GHz	5.48 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 Description of EUT

Product	Network Camera
Brand	VIVOTEK
Test Model	FD9380-HNWL
Series Model	FD9380-H
Model Difference	Refer to below note
Sample Status	ENGINEERING SAMPLE
Operating Software	N/A
Power Supply Rating	DC 12V or PoE
Accessory Device	N/A
Data Cable Supplied	Shielded Y cable (LAN + DC) with one ferrite core. (0.3m)

Note:

The EUT is a Network Camera, and it has several models, which are identical with each other, except for following difference:

Model	Power supply rating
FD9380-HNWL	DC 12V or PoE
FD9380-H	DC 12V only

During the test, the **Model: FD9380-HNWL** was selected as the representative one and therefore only its test data was recorded in this report.

#### 3.2 Features of EUT

The tests reported herein were performed according to the method specified by VIVOTEK INC., for detailed feature description, please refer to the manufacturer's specifications or user's manual.

### 3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode

1. EUT has been pre-tested under following test modes, and test **mode 2** was the worst case.

Mode	Test Condition
1	Adapter Mode
2	PoE Mode

2. Test modes are presented in the report as below.

Mode	Test Condition	Input Power
<b>Conducted emission test</b>		
1	Adapter Mode	12Vdc
2	PoE Mode	55Vdc
<b>Radiated emission test</b>		
1	Adapter Mode	12Vdc
2	PoE Mode	55Vdc

### 3.4 Test Program Used and Operation Descriptions

- a. Connected the EUT with Adapter or PoE adapter.
- b. Turned on the power of all equipment.
- c. EUT captured video / audio signal to notebook (kept in a remote area) via an UTP LAN cable, then it displayed messages on its screen simultaneously. **<For Adapter Mode >**
- d. EUT captured video / audio signal to notebook (kept in a remote area) via PoE adapter with an UTP LAN cable, then it displayed messages on its screen simultaneously. **<For PoE Mode>**
- e. EUT Save images to Micro SD card.
- f. Steps c-e were repeated.


### 3.5 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 1.6GHz, provided by VIVOTEK INC., for detailed internal source, please refer to the manufacturer's specifications.


#### 4 Configuration and Connections with EUT

##### 4.1 Connection Diagram of EUT and Peripheral Devices

Conducted emission test



### Radiated emission test



#### 4.2 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Micro SD Card	Transcend	16GB	N/A	N/A	Provided by Lab
B.	Adapter	Atech OEM	ADS018K-X120150	N/A	N/A	Supplied by client
C.	PoE Adapter	Microsemi	PD-9001GR	N/A	N/A	Supplied by client
D.	Notebook PC	ASUS	PU401L	ECNXBC0125 28528	FCC DoC Approved	Provided by Lab

Note:

- All power cords of the above support units are non-shielded (1.8m).
- Items D acted as communication partners to transfer data.
- Rating of item B was listed as below:  
AC I/P: 100-240V, 50-60Hz, 0.5A  
DC O/P: 12V, 1.5A
- Rating of item C was listed as below:  
AC I/P: 100-240V, 50/60Hz, 0.67A  
DC O/P: 55V, 0.6A

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Y cable (LAN + DC)	1	0.3	Y	1	Supplied by client
2.	DC cable	1	1.5	N	0	Supplied by client
3.	LAN cable (Cat.5e)	1	10	N	0	Provided by Lab
4.	LAN cable (Cat.5e)	1	1.0	N	0	Provided by Lab
5.	AC power cord	1	1.8	N	0	Supplied by client
6.	LAN cable (Cat.5e)	1	1.8	N	0	Provided by Lab

Note: The core(s) is(are) originally attached to the cable(s).

## 5 Conducted Emissions at Mains Ports

### 5.1 Limits

Frequency (MHz)	Class A (dBUV)		Class B (dBUV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Notes: 1. The lower limit shall apply at the transition frequencies.  
 2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 5.2 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESR3	102413	Feb. 8, 2018	Feb. 7, 2019
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 18, 2018	Dec. 17, 2019
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 18, 2018	Dec. 17, 2019
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Nov. 5, 2018	Nov. 4, 2019
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 3, 2018	May 2, 2019
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK 8121	8121-808	Mar. 5, 2018	Mar. 4, 2019
Software	Cond_V7.3.7.4	NA	NA	NA
RF cable (JYEBAO) With 10dB PAD	5D-FB	Cable-C09.01	Feb. 21, 2018	Feb. 20, 2019
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 8, 2018	May 7, 2019

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in Shielded Room No. 9.  
 3. The VCCI Site Registration No. C-1312.  
 4. Tested Date: Jan. 31, 2019.

### 5.3 Test Arrangement

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



**Note: Support units were connected to second LISN.**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


### 5.4 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	12Vdc	Environmental Conditions	22°C, 71%RH
Tested by	Chin-Wen Wang		
Test Mode	Mode 1		

Phase Of Power : Positive (+)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.14	40.58	16.74	50.72	26.88	65.79	55.79	-15.07	-28.91
2	0.17734	10.15	37.02	15.26	47.17	25.41	64.61	54.61	-17.44	-29.20
3	0.20078	10.15	34.27	14.87	44.42	25.02	63.58	53.58	-19.16	-28.56
4	0.23984	10.16	30.49	11.60	40.65	21.76	62.10	52.10	-21.45	-30.34
5	0.52500	10.20	31.40	25.13	41.60	35.33	56.00	46.00	-14.40	-10.67
6	0.95078	10.27	17.94	9.73	28.21	20.00	56.00	46.00	-27.79	-26.00
7	15.55469	10.93	15.21	9.82	26.14	20.75	60.00	50.00	-33.86	-29.25

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	12Vdc	<b>Environmental Conditions</b>	22°C, 71%RH
<b>Tested by</b>	Chin-Wen Wang		
<b>Test Mode</b>	Mode 1		

Phase Of Power : Negative (-)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.18	41.21	20.01	51.39	30.19	66.00	56.00	-14.61	-25.81
2	0.19687	10.19	35.82	14.64	46.01	24.83	63.74	53.74	-17.73	-28.91
3	0.24375	10.20	30.20	11.81	40.40	22.01	61.97	51.97	-21.57	-29.96
4	0.52500	10.24	31.34	25.15	41.58	35.39	56.00	46.00	-14.42	-10.61
5	0.99766	10.33	17.71	10.20	28.04	20.53	56.00	46.00	-27.96	-25.47
6	16.62109	10.84	20.51	15.05	31.35	25.89	60.00	50.00	-28.65	-24.11

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	22°C, 71%RH
<b>Tested by</b>	Chin-Wen Wang		
<b>Test Mode</b>	Mode 2		

Phase Of Power : Positive (+)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	10.14	29.73	20.72	39.87	30.86	65.18	55.18	-25.31	-24.32
2	0.43125	10.19	29.54	24.50	39.73	34.69	57.23	47.23	-17.50	-12.54
3	0.57969	10.21	17.67	12.27	27.88	22.48	56.00	46.00	-28.12	-23.52
4	18.24219	11.06	27.94	24.58	39.00	35.64	60.00	50.00	-21.00	-14.36
<b>5</b>	<b>24.41797</b>	<b>11.14</b>	<b>34.21</b>	<b>33.09</b>	<b>45.35</b>	<b>44.23</b>	<b>60.00</b>	<b>50.00</b>	<b>-14.65</b>	<b>-5.77</b>
6	28.68750	11.15	27.93	25.89	39.08	37.04	60.00	50.00	-20.92	-12.96

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9kHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	22°C, 71%RH
<b>Tested by</b>	Chin-Wen Wang		
<b>Test Mode</b>	Mode 2		

Phase Of Power : Negative (-)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	10.18	29.41	19.24	39.59	29.42	65.18	55.18	-25.59	-25.76
2	0.43906	10.23	28.37	23.63	38.60	33.86	57.08	47.08	-18.48	-13.22
3	0.57578	10.25	16.82	11.73	27.07	21.98	56.00	46.00	-28.93	-24.02
4	17.69531	10.87	26.87	23.70	37.74	34.57	60.00	50.00	-22.26	-15.43
5	24.89844	10.73	34.94	32.63	45.67	43.36	60.00	50.00	-14.33	-6.64
6	27.16016	10.65	28.45	26.34	39.10	36.99	60.00	50.00	-20.90	-13.01

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



## 6 Radiated Emissions up to 1 GHz

### 6.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		

Radiated Emissions Limits at 3 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960			57.5	47.5
960-1000	60	54		

- Notes:
1. The lower limit shall apply at the transition frequencies.
  2. Emission level (dB $\mu$ V/m) = 20 log Emission level (uV/m).
  3. QP detector shall be applied if not specified.

### 6.2 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100291	Sep. 3, 2018	Sep. 2, 2019
Schwarzbeck Bilog Antenna	VULB9168	9168-303	Nov. 22, 2018	Nov. 21, 2019
Agilent Preamplifier	8447D	2944A08119	Feb. 21, 2018	Feb. 20, 2019
ADT. Turn Table	TT100	0205	NA	NA
ADT. Tower	AT100	0205	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
ADT RF Switches BOX	EMH-011	1001	Oct. 25, 2018	Oct. 24, 2019
Pacific RF cable With 5dB PAD	8D	CABLE-ST2-01	Oct. 25, 2018	Oct. 24, 2019

- Notes:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in Open Site No. 2.
  3. The VCCI Site Registration No. R-237.
  4. Tested Date: Jan. 31, 2019

### 6.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 6.4 Test Results


<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Input Power</b>	12Vdc	<b>Environmental Conditions</b>	22°C, 73%RH
<b>Tested by</b>	Paul Chen		
<b>Test Mode</b>	Mode 1		

### Antenna Polarity & Test Distance : Horizontal at 10 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	46.53	21.77 QP	30.00	-8.23	4.00 H	33	30.54	-8.77
2	124.98	21.51 QP	30.00	-8.49	4.00 H	42	31.90	-10.39
3	168.00	23.11 QP	30.00	-6.89	4.00 H	306	32.28	-9.17
4	216.00	21.31 QP	30.00	-8.69	4.00 H	270	32.85	-11.54
5	249.98	27.26 QP	37.00	-9.74	3.75 H	244	37.40	-10.14
6	500.02	28.37 QP	37.00	-8.63	1.89 H	321	31.93	-3.56
7	625.02	27.72 QP	37.00	-9.28	1.42 H	106	28.07	-0.35
8	750.03	29.09 QP	37.00	-7.91	1.00 H	115	27.96	1.13
9	875.00	28.81 QP	37.00	-8.19	1.00 H	314	26.23	2.58

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Input Power</b>	12Vdc	<b>Environmental Conditions</b>	22°C, 73%RH
<b>Tested by</b>	Paul Chen		
<b>Test Mode</b>	Mode 1		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.73	24.57 QP	30.00	-5.43	1.34 V	79	33.73	-9.16
2	59.44	23.35 QP	30.00	-6.65	1.42 V	132	32.97	-9.62
3	110.77	23.47 QP	30.00	-6.53	1.00 V	1	35.45	-11.98
4	124.98	24.06 QP	30.00	-5.94	1.00 V	70	34.45	-10.39
5	168.00	26.29 QP	30.00	-3.71	1.00 V	180	35.46	-9.17
6	216.01	21.07 QP	30.00	-8.93	1.00 V	75	32.61	-11.54
7	250.00	27.66 QP	37.00	-9.34	1.00 V	37	37.80	-10.14
8	500.02	27.45 QP	37.00	-9.55	3.36 V	349	31.01	-3.56
9	625.04	28.73 QP	37.00	-8.27	2.90 V	184	29.08	-0.35
10	749.99	30.44 QP	37.00	-6.56	2.57 V	336	29.31	1.13
11	875.01	29.62 QP	37.00	-7.38	2.09 V	105	27.05	2.57

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	22°C, 73%RH
<b>Tested by</b>	Paul Chen		
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	47.55	20.94 QP	30.00	-9.06	4.00 H	57	29.67	-8.73
2	125.01	20.49 QP	30.00	-9.51	4.00 H	261	30.88	-10.39
3	168.02	22.54 QP	30.00	-7.46	4.00 H	100	31.71	-9.17
4	223.92	20.50 QP	30.00	-9.50	4.00 H	313	31.90	-11.40
5	250.00	28.93 QP	37.00	-8.07	3.88 H	242	39.07	-10.14
6	500.01	27.90 QP	37.00	-9.10	1.97 H	131	31.46	-3.56
7	625.01	28.68 QP	37.00	-8.32	1.44 H	87	29.03	-0.35
8	749.99	28.72 QP	37.00	-8.28	1.00 H	180	27.59	1.13
9	875.01	29.07 QP	37.00	-7.93	1.00 H	89	26.50	2.57

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	30MHz ~ 1GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP), 120kHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	22°C, 73%RH
<b>Tested by</b>	Paul Chen		
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	55.92	25.09 QP	30.00	-4.91	1.35 V	309	34.32	-9.23
2	125.02	24.13 QP	30.00	-5.87	1.00 V	332	34.52	-10.39
<b>3</b>	<b>168.00</b>	<b>26.93 QP</b>	<b>30.00</b>	<b>-3.07</b>	<b>1.00 V</b>	<b>326</b>	<b>36.10</b>	<b>-9.17</b>
4	218.96	23.15 QP	30.00	-6.85	1.00 V	37	34.68	-11.53
5	249.99	29.29 QP	37.00	-7.71	1.00 V	305	39.43	-10.14
6	500.00	27.01 QP	37.00	-9.99	3.15 V	217	30.57	-3.56
7	625.00	27.84 QP	37.00	-9.16	3.05 V	115	28.19	-0.35
8	750.00	29.21 QP	37.00	-7.79	2.65 V	45	28.08	1.13
9	875.00	29.40 QP	37.00	-7.60	2.28 V	243	26.83	2.57

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



## 7 Radiated Emissions above 1 GHz

### 7.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
Above 3000	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
1000-3000	Avg: 60	Avg: 54	Avg: 56 Peak: 76	Avg: 50 Peak: 70
Above 3000	Peak: 80	Peak: 74	Avg: 60 Peak: 80	Avg: 54 Peak: 74

- Notes: 1. The lower limit shall apply at the transition frequencies.  
 2. Emission level (dB $\mu$ V/m) = 20 log Emission level (uV/m).  
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### Frequency Range of Radiated Measurement (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40GHz, whichever is lower

## 7.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Agilent Spectrum	E4446A	MY51100009	Jun. 4, 2018	Jun. 3, 2019
Agilent Test Receiver	N9038A	MY51210137	Jun. 19, 2018	Jun. 18, 2019
Agilent Preamplifier	8449B	3008A01201	Feb. 21, 2019	Feb. 20, 2020
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Feb. 21, 2019	Feb. 20, 2020
EMCI Preamplifier	EMC184045B	980235	Feb. 21, 2019	Feb. 20, 2020
ETS Preamplifier	3117-PA	00215857	Nov. 25, 2018	Nov. 24, 2019
Schwarzbeck Horn Antenna	BBHA-9170	212	Nov. 25, 2018	Nov. 24, 2019
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Nov. 25, 2018	Nov. 24, 2019
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V8.7.08	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF102	Cable-CH6-01	Aug. 13, 2018	Aug. 12, 2019
SUHNER RF cable With 3/4dB PAD	SF102	Cable-CH8-02 (3.6m)	Aug. 13, 2018	Aug. 12, 2019
MICRO-TRONICS Notch filter	BRC50703-01	010	May 31, 2018	May 30, 2019
MICRO-TRONICS Band Pass Filter	BRM17690	005	May 31, 2018	May 30, 2019


Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in Chamber No. 6.
3. The Industry Canada Reference No. IC 7450E-6.
4. The VCCI Site Registration No. G-257.
5. Tested Date: Jan. 30, 2019.

### 7.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

Note: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.



\* :depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

### 7.4 Test Results


<b>Frequency Range</b>	1GHz ~ 8GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Input Power</b>	12Vdc	<b>Environmental Conditions</b>	20°C, 71%RH
<b>Tested by</b>	Vincent Lin		
<b>Test Mode</b>	Mode 1		

#### Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1250.03	45.82 PK	74.00	-28.18	1.15 H	72	50.67	-4.85
2	1250.03	30.90 AV	54.00	-23.10	1.15 H	72	35.75	-4.85
3	1374.95	46.89 PK	74.00	-27.11	1.00 H	228	50.68	-3.79
4	1374.95	33.18 AV	54.00	-20.82	1.00 H	228	36.97	-3.79
5	1625.01	48.12 PK	74.00	-25.88	1.73 H	5	52.73	-4.61
6	1625.01	32.33 AV	54.00	-21.67	1.73 H	5	36.94	-4.61

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 8GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Input Power</b>	12Vdc	<b>Environmental Conditions</b>	20°C, 71%RH
<b>Tested by</b>	Vincent Lin		
<b>Test Mode</b>	Mode 1		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1250.01	45.62 PK	74.00	-28.38	1.94 V	4	50.47	-4.85
2	1250.01	31.05 AV	54.00	-22.95	1.94 V	4	35.90	-4.85
3	1375.05	45.27 PK	74.00	-28.73	2.25 V	172	49.06	-3.79
4	1375.05	30.73 AV	54.00	-23.27	2.25 V	172	34.52	-3.79
5	1499.99	44.83 PK	74.00	-29.17	2.65 V	175	49.30	-4.47
6	1499.99	29.67 AV	54.00	-24.33	2.65 V	175	34.14	-4.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 8GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	20°C, 71%RH
<b>Tested by</b>	Vincent Lin		
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1249.95	45.77 PK	74.00	-28.23	2.14 H	1	50.63	-4.86
2	1249.95	32.41 AV	54.00	-21.59	2.14 H	1	37.27	-4.86
3	1499.96	46.63 PK	74.00	-27.37	1.91 H	39	51.10	-4.47
4	1499.96	35.84 AV	54.00	-18.16	1.91 H	39	40.31	-4.47
5	1624.83	51.33 PK	74.00	-22.67	2.49 H	358	55.94	-4.61
6	1624.83	28.52 AV	54.00	-25.48	2.49 H	358	33.13	-4.61

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




<b>Frequency Range</b>	1GHz ~ 8GHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Peak (PK) / Average (AV), 1MHz
<b>Input Power</b>	55Vdc	<b>Environmental Conditions</b>	20°C, 71%RH
<b>Tested by</b>	Vincent Lin		
<b>Test Mode</b>	Mode 2		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1250.13	53.30 PK	74.00	-20.70	2.34 V	79	58.15	-4.85
<b>2</b>	<b>1250.13</b>	<b>39.24 AV</b>	<b>54.00</b>	<b>-14.76</b>	<b>2.34 V</b>	<b>79</b>	<b>44.09</b>	<b>-4.85</b>
3	1625.03	53.92 PK	74.00	-20.08	3.07 V	146	58.53	-4.61
4	1625.03	29.61 AV	54.00	-24.39	3.07 V	146	34.22	-4.61
5	1750.02	51.72 PK	74.00	-22.28	1.04 V	0	56.08	-4.36
6	1750.02	32.14 AV	54.00	-21.86	1.04 V	0	36.50	-4.36

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



## 8 Pictures of Test Arrangements

### 8.1 Conducted Emissions at Mains Ports

Mode 1




Mode 2





## 8.2 Radiated Emissions up to 1 GHz

Mode 1





Mode 2





### 8.3 Radiated Emissions above 1 GHz

Mode 1



Mode 2



## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety/Telecom Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---