



S Series

NV9311P

H.265 8-CH Embedded PoE
Mobile NVR



技術仕様

Technical Specifications

| | |
|--------------|------------------------------|
| Descriptions | 8-CH Embedded PoE Mobile NVR |
|--------------|------------------------------|

Device

| | |
|-------------------|---|
| OS | Embedded Linux |
| Watchdog | Hardware + Software |
| Power Restoration | System Restart Automatically after Power Recovery |

Display

| | |
|--------------------|--|
| LiveView Display | 8 Channels Multi-layout display: 1x1, 3V, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6 |
| Video Output | HDMI x1, VGA x1 |
| Display Resolution | 3840x2160, 1920x1080, 1280x720 |
| Stream Application | Constant Bitrate / Auto Adaptive Stream |
| Fisheye Dewarp | 10, 1P, 1R, 1O3R, 1O8R |
| PTZ Operation | Direction Control, Home, Iris, Preset, Patrol (Group) |

Video

| | |
|---------------------|--|
| Video Format | MJPEG, H.264, H.265 |
| Graphic Decoder | Hardware decoding |
| Decoding Resolution | UP to 3840x2160 |
| Decoding Capability | 3840x2160 @ 120 fps (4-CH) 1920x1080 @ 240 fps (8-CH) |

Audio

| | |
|--------------|--------------|
| Audio Format | G.711, G.726 |
| Audio In/Out | Line out x 1 |

Record

| | |
|-----------------------|--|
| Recording Time (sec.) | Pre-Record: 5 (Max. 10) Post-Record: 20 (Max. 300) |
| Recording Stream | Single |
| Recording Throughput | 64 Mbps |
| Recording Mode | Continuous, Schedule, Manual, Event, Activity Adaptive Streaming |
| Recording Setting | Recycle (unit: Day) |
| Watermark | Supported |

Storage & Backup

| | |
|-------------------|--|
| DISK Devices | Internal x1 (2.5" HDD/SSD) (HDD is purchased by separately) |
| HDD Max. Capacity | Please refer to HDD supported list on VIVOTEK website |
| Disk Management | Create, Format and Remove Disk HDD S.M.A.R.T |
| SD Card | SD card slot x1 (reserved) |
| Video Clip Export | USB Dongle (FAT Format) |
| Schedule Backup | FTP |

Playback

| | |
|---------------------------------|--|
| Playback Display | 4 Channels Multi Layout Display: 1x1,2x2,1P+3,1V+3 |
| Playback Control | Regular (Play, Pause, Stop), Rewind, Next / Previous Frame, Speed Control, Calendar, Event, Timeline, Timeline Scale, Thumbnail (Storyboard) |
| Video Search | By Calendar, Date/Time, and Alarm |
| Thumbnail Explorer (Storyboard) | Listing the thumbnail of recorded video (Max. 2 CH) |
| Snapshot | JPEG |
| Video Clip Export | EXE |

Network

| | |
|-----------------------------|--|
| Ethernet | 10/100/1000Mbps Ethernet (RJ-45) x 1 |
| Network Throughput in total | 96 Mbps |
| WiFi | 802.11a/b/g/n/ac 2T2R (optional) |
| Mobile Network | LTE (optional) |
| PoE | 802.3at/af compliant PoE ports x 8 (RJ45) (Total Max. 64W) |
| PoE Management | Supported |
| Protocols | IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter |

External Interface

| | |
|-------------------|---|
| USB | Front x2 (USB 2.0) Back x1 (USB 2.0) |
| Alarm In | 8 |
| Alarm Out | 4 |
| Audio | Line out x 1 |
| Antenna Interface | GPS x1, WiFi x2, LTE x2 |
| RS232 | 1 Port (Reserved) |

| System | |
|--------------------|--|
| Camera Integration | ONVIF Profile S |
| GNSS | GPS/GALILEO/GLONASS supported |
| G-sensor | Supported |
| Event | Motion Detection, PIR Detection, Tampering Detection, Camera DI/DO, Camera Disconnected, Disk Failure, Disk Full, NVR DI/DO, GPS disconnected, GPS speed, G-sensor |
| Event Action | Video recording, email with snapshot, buzzer, PTZ, FTP, DO (camera, system), full screen, send to CMS |
| User Management | User level: administrator, regular user |
| Log | System, Recording, User, Error |
| Date&Time | Time Zone, Manual, Automatic Sync NTP, Daylight Saving Time |
| Language | Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese |

| Remote Client | |
|-------------------|--|
| Software AP | Shepherd ,VAST 2 |
| Mobile/Tablet App | iViewer (Android & iOS) |
| Web Browser | Internet Explorer 10 (32 bit) or later/ Windows Chrome v68.0.3 & Firefox v61.02 or later/ Windows & macOS |

| General | |
|-----------------------|---|
| Power Input | DC 12V~48V ±10% |
| Power Management | Programmable delay on/off relative to ignition or other switched voltage |
| Power Consumption | Max. 149 W Without HDD/SSD and PoE: Max. 15 W (Heater off), Max. 60 W (Heater on) |
| Dimensions | 284 (W) x 230 (D) x 90 (H) mm |
| Weight | 4.06 kg (without HDD) |
| Operating Temperature | -40°C ~ 55°C (-40°F ~ 131°F) |
| Humidity | 0 ~ 95% |
| Safety Certifications | CE, FCC, VCCI, C-Tick, EN50155, EN61373, UL, CB, EN45545, EN50121-3-2/EN50121-4, MIL-STD-810G |