



# RX9401

## H.265 16-CH Embedded Video Receiver



### Technische Daten

#### Technical Specifications

Descriptions	16-CH Embedded Video Decoder
--------------	------------------------------

#### Device

OS	Embedded Linux
Watchdog	Hardware + Software
Power Restoration	Automatischer Neustart des Systems nach Wiederherstellung der Stromversorgung

#### Display

LiveView Display	16 Kanäle Mehrfach-Layout-Anzeige: 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4
Video Output	HDMI x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant/Auto Adaptive Stream
Fisheye Dewarp	10, 1P, 1R, 1O3R, 1O8R
PTZ Operation	Richtungssteuerung, Home, Fokus, Iris, Voreinstellung, Patrouille (Gruppe)

#### Video

Video Format	H.264, H.265
Graphic Decoder	Hardware-Decodierung
Decoding Resolution	Bis zu 3840x2160
Decoding Capability	3840x2160 @ 30 fps (1CH) 1920x1080 @ 120 fps (4CH) 720x480 @ 480fps (16CH)

#### Audio

Audio Format	G.711, G.726
--------------	--------------

## Network

Ethernet	10/100Mbps Ethernet (RJ-45) x 1
Network Throughput in total	40 Mbps
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

## External Interface

USB	Vorderseite: 1 (USB 2.0) Rückseite: 1 (USB 2.0)
-----	--

## System

Camera Integration	ONVIF core spec 2.2 or above (*by project)
User Management	Benutzerlevel: Administrator, regulärer Benutzer
Date&Time	Zeitzone, Manuell, Automatische Synchronisation NTP, Sommerzeit
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

## Remote Client

Software AP	Shepherd ,VAST 2(reserved)
Web Browser	Internet Explorer 10 (32 bit) or above

## General

Power Input	DC 12V 1.5A
Power Consumption	Max. 9.24 W
Dimensions	198 (W) x 200 (D) x 47(H)mm
Weight	530 g
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick