



C Series

FD9186-H

5MP Mini Indoor Fixed Dome Camera



Technical Specifications

System Information

| | |
|-------|---------------------------------|
| CPU | Multimedia SoC (System-on-Chip) |
| Flash | 256MB |
| RAM | 512MB |

Camera Specifications

| | |
|-------------------------|---|
| Image Sensor | 1/2.7" Progressive CMOS |
| Max. Resolution | 2880x1616 (5MP) |
| Lens Type | Fixed-focal |
| Focal Length | f = 2.8 mm |
| Aperture | F1.6 |
| Iris Type | Fixed iris |
| Field of View | 111.0° (Horizontal) 59.0° (Vertical) 133.0° (Diagonal) |
| Shutter Time | 1/5 sec. to 1/32,000 sec. |
| WDR Technology | WDR Pro |
| Day/Night | Yes |
| Removable IR-cut filter | Yes |
| Illuminators | Built-in IR Illuminator up to 30 meters with Smart IR, IR LED*2 |
| Minimum Illumination | 0.055 lux @ F1.6 (Color) 0.005 lux @ F1.6 (B/W) 0 lux with IR illumination on |
| Pan Range | 350° |
| Tilt Range | 65° |
| Rotation Range | 200° |

| | |
|----------------------------|---|
| Storage | Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS) |
| Built-in Installation Aids | Pixel Calculator |

| Video | |
|--------------------|---|
| Compression | H.265, H.264, MJPEG |
| Maximum Frame Rate | 30 fps @ 2880x1616 |
| Maximum Streams | 3 video streams (Up to 7 configurable profiles) |
| Main Stream | 30fps @2880x1616, 2688x1512, 2560x1440, 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9) |
| 2nd Stream | 30fps @1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9) |
| 3rd Stream | 30 fps @ 1280x720, 640x360, 480x272 (16:9) |
| S/N Ratio | 58 dB |
| Dynamic Range | 120 dB |
| Video Streaming | Adjustable resolution, quality and constant bit rate control, Smart Stream III |
| Image Settings | General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings |
| | Illuminators illuminators, anti-overexposure/smart IR |
| | Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR |
| | Exposure BLC, HLC, exposure control (exposure level, exposure time, gain control), AE speed adjustment, WDR |
| | Privacy mask Pixel calculator Scheduled profile settings |

| Audio | |
|------------------|-----------------------------|
| Audio Capability | One-way Audio |
| Compression | MPEG-2 AAC-LC, G.711, G.726 |
| Interface | Built-in microphone |
| Effective Range | 5 meters |

| Network | |
|-----------|--|
| Users | Live viewing for up to 10 clients |
| Security | Access list, CSRF protection, digest authentication, HTTPS , IEEE 802.1x, Password protection, signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), user access log, user account management |
| Protocols | 802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTCIP, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2/1.3, UDP, UPnP |
| Interface | 10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard. |
| ONVIF | Profile G, S, T supported, Onvif 21.06 |

| AI Analytics | |
|-------------------------|--|
| Compute Capability | SoC with built-in hardware deep learning accelerator |
| Vision Object Analytics | Object Detection People, Vehicle (4-wheeled), Human / Vehicle Bestshot, Path Extraction |
| Application | Deep Learning VCA (Smart Motion Detection, Smart VCA) Smart VCA - Group 1 Smart Motion Detection (Five-window video motion detection, People detection, Vehicle detection, Time filter), Smart VCA (Intrusion detection, Loitering detection, Line crossing detection) |

| Solution Integration | |
|------------------------|---|
| VADP Package | Trend Micro (Default, 1-year free trial) |
| Video Motion Detection | Motion Detection (Five-window video motion detection) |

| Alarm and Event | |
|-----------------|---|
| Event Trigger | Periodically trigger, system boot, manual trigger, digital input, motion detection, tampering detection, recording notification |
| Event Action | Event notification via digital output, audio clips, camera link, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card |

| General | |
|-----------------------|--|
| Connectors | RJ-45 cable connector for 10/100/100 Mbps Network/PoE connection DC 12V power input Digital input |
| LED Indicator | System power and status indicator |
| Power Input | IEEE 802.3af PoE Class 3 DC 12V |
| Power Consumption | PoE: Max. 6.9W/ 5.8W (IR on/off) typical 4.1W/3W (IR on/off) DC12V: Max 6.5W/ 5.4W (IR on/off) |
| Dimensions | Ø 91 x 63 mm |
| Weight | 156 g |
| Certifications | EMC CE (EN 55032/EN 55035 Class A), UKCA (BS EN 55032/BS EN 55035 Class A), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A), IC (ICES-003 Issue 7, Class A) Safety: UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 62471), LVD (IEC/EN 62368-1), UKCA (BS EN 62368-1) IA BIS (IS 13252), BSMI (EMC: CNS 15936, Safety: CNS 15598-1) |
| Operating Temperature | Starting Temperature: -10°C ~ 55°C (14°F ~ 131°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) (IR on) -10°C ~ 55°C (14°F ~ 131°F) (IR off) |
| Humidity | 90% RH (non-condensing) |

| System Requirements | |
|---------------------|---|
| Operating System | Microsoft Windows 10/8/7 Mac 10.12 (Chrome only) |
| Web Browser | Chrome 58.0 or above |
| Other Players | VLC: 1.1.11 or above |

Included Accessories

| | |
|------------------|--|
| Packing Contents | Quick installation guide, alignment sticker, screw pack, |
|------------------|--|

DORI (EN 62676-4 Standard)

| | |
|--------------------------------|------------------|
| Detection (25PPM/ 8PPF) | 63.6m (208.5 ft) |
| Observation (63PPM/ 19PPF) | 25.4 m (83.4 ft) |
| Recognition (125PPM/ 38PPF) | 12.7 m (41.6 ft) |
| Identification (250PPM/ 76PPF) | 6.3 m (20.7 ft) |