

Product Type	Model	Description
110 – Network Camera – Dome	FD9166-HN(2.8MM)	Indoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
110 – Network Camera – Dome	FD9166-HN(3.6MM)	Indoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed lens, 3 Axis with940IR 10M, WDR Pro, 3DNR, PoE, One way audio, Built-in micro
110 – Network Camera – Dome	FD9167-HT-v2	Indoor Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD9182-H	Recessed design dome,5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/ N, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C~ 50°C (-10°F ~ 122°F)
110 – Network Camera – Dome	FD9187-HT-A	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, Working Temperature: -10° C ~ 45° C (14° F ~ 113° F)
110 – Network Camera – Dome	FD9365-EHTV-A	Outdoor Vandal Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
110 – Network Camera – Dome	FD9365-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
110 – Network Camera – Dome	FD9366-HV(2.8MM)	Outdoor Mini Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
110 – Network Camera – Dome	FD839-EHTV-v2	VORTEX Premium Series Outdoor Vandal Remote Dome, 5M 15fps, H.264/MJPEG, f = 2.8~12 mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), NEMA 4X/IP66/IK10/Working Temperature:-35°C ~ 50°C (-31° F ~ 122°F),Built-in microphone
110 – Network Camera – Dome	FD939-EHTV	VORTEX Premium Series Outdoor Vandal Remote Dome, 8M 15fps, H.264/MJPEG, f = 4.3~9.8mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), NEMA 4X/IP66/IK10/Working Temperature:-35°C ~ 50°C (-31° F ~ 122°F),Built-in microphone
110 – Network Camera – Dome	FD833-HV	VORTEX Premium Series Outdoor Vandal Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-30°C ~ 55°C (-22°F
110 – Network Camera – Dome	FD9366-HV(3.6MM)	Outdoor Mini Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, PoE, I/O*1/1, One way audio, Built-in Mic
110 – Network Camera – Dome	FD9367-EHTV-v2	Outdoor Vandal-proof Dome, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD9368-HTV	Outdoor Vandal Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
110 – Network Camera – Dome	FD9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm,IR 30m, Smart motion ,PoE/DC12V, Built in Mic, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
110 – Network Camera – Dome	FD9380-H	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
110 – Network Camera – Dome	FD9380-H(2.8MM)	Outdoor Fixed Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
110 – Network Camera – Dome	FD9387-EHTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -50° C ~60° C (-58° F ~ 140° F)
110 – Network Camera – Dome	FD9387-HTV-A	Outdoor Vandal Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
110 – Network Camera – Dome	FD9388-HTV	Outdoor Vandal Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
110 – Network Camera – Dome	FD9189-H-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD9189-HT-v2	Indoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)

110 – Network Camera – Dome	FD9389-EHV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD9389-EHTV-v2	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD9391-EHTV-v2	Outdoor Vandal-proof Dome, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, Smart IR III, PoE, DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
110 – Network Camera – Dome	CD9381-HNTV	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.8~8mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F)
110 – Network Camera – Dome	CD9381-HNVF2	Indoor/Outdoor Vandal Proof, 5M 30fps, H.265/H.264/MJPEG, f2.4mm fixed focal lens, D/N, 940nm IR up to 10m IR, WDR Pro, 3DNR, PoE/DC12V/AC24V, 2 way audio, builtin mic, MicroSD/SDHC/SDXC, IP67, IK10+, Working Temperature: -10°C ~ 55°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD9387-EHTV-V3(7-22MM)	Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD9387-EHTV-V3(2.7-13.5MM)	Outdoor Vandal-proof Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD9187-HT-V3(2.7-13.5MM)	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD9187-HT-V3(7-22MM)	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 1/1 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66/IP67/IK10/NEMA 4X, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD9383-HV(2.8MM)	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F)
110 – Network Camera – Dome	FD9383-HV(3.6MM)	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F)
110 – Network Camera – Dome	FD9383-HTV	Outdoor Fixed Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F)
110 – Network Camera – Dome	FD9189-H-V3	Indoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 30m, HDMI output, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, Working Temperature: 0°C ~ 45°C (-32°F ~ 113°F)
110 – Network Camera – Dome	FD9389-EHV-V3	Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optional accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F)
110 – Network Camera – Dome	FD9389-EHTV-V3	Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, 3.3~9.7mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optional accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F)
110 – Network Camera – Dome	FD9199-H	Indoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 30m, HDMI output, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optional accessory, MicroSD/SDHC/SDXC, Working Temperature: 0°C ~ 45°C (-32°F ~ 113°F)
110 – Network Camera – Dome	FD9399-EHV	Outdoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optional accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F)

110 – Network Camera – Dome	FD9399-EHTV	Outdoor Dome, 8M 30fps, H.265/H.264/MJPEG, 4.3~9.8mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1 by optional accessory, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F)
110 – Network Camera – Dome	FD9186-H	Indoor Mini Dome, 5M 30fps, H.265, f2.8mm fixed lens, 3 Axis adjustment, IR 30M, WDR Pro, 3DNR, PoE, One way audio, Built-in microphone, DI*1, DC jack, MicroSD/SDHC/SDXC
110 – Network Camera – Dome	FD9380-HV-V2	AI Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22°F ~ 140°F)
110 – Network Camera – Dome	FD9380-HTV-V2	AI Outdoor Dome, 5M 30fps, H.265/H.264/MJPEG, f2.7~13.5mm remote focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F)
110 – Network Camera – Dome	FD639	VORTEX Essential Series Outdoor Vandal Dome, 2M 15fps, H.264/MJPEG, 2.8mm, D/N, IR 30m, WDR Enhance, Smart Stream III, 3DNR, PoE/DC12V, Built in Mic, Built-in 128G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 50°C (-22°F ~ 122° F)
110 – Network Camera – Dome	FD819-H	VORTEX Essential Series Indoor Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD819-HT	VORTEX Essential Series Indoor Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
110 – Network Camera – Dome	FD839-EHV	VORTEX Essential Series Outdoor Vandal Fixed Dome, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-40°C ~ 60°C (-40°F
110 – Network Camera – Dome	FD839-EHTV	VORTEX Essential Series Outdoor Vandal Vari-focal Dome, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
110 – Network Camera – Dome	FD837-HTV	VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 5M 15fps, H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IP67/IK10, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
111 – Network Camera – Turret	IT9399-HVW	Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, f4.2mm fixed focal lens, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
111 – Network Camera – Turret	IT9399-HTVW	Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, motorized lens 4.3~9.8mm, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
111 – Network Camera – Turret	IT9389-HVW-V3	Flat-faced AI turret, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
111 – Network Camera – Turret	IT9389-HTVW-V3	Flat-faced AI turret, 8M 30fps, H.265/H.264/MJPEG, motorized lens 2.8~12mm, smart hybrid illuminator 30m, WDR Pro, build-in mic, speaker, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
111 – Network Camera – Turret	IT9360-H	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
111 – Network Camera – Turret	IT9360-H(2.8MM)	Turret Dome, 2M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
111 – Network Camera – Turret	IT9380-H	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30 ° C ~ 60° C (-22° F
111 – Network Camera – Turret	IT9380-H(2.8MM)	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens,D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
111 – Network Camera – Turret	IT9388-HT	Turret Dome, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
111 – Network Camera – Turret	IT9389-H-v2	Turret Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature:-20°C ~ 50°C (-4°F ~ 122°F)
111 – Network Camera – Turret	IT9383-HVW	Flat-faced AI Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
111 – Network Camera – Turret	IT9383-HTVW	Flat-faced AI Dome, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)

111 – Network Camera – Turret	IT9380-HV-V2	AI Outdoor Turret, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22°F ~ 140°F)
111 – Network Camera – Turret	IT9380-HTV-V2	AI Outdoor Turret, 5M 30fps, H.265/H.264/MJPEG, f2.7~13.5mm remote focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F)
111 – Network Camera – Turret	IT839-H	VORTEX Essential Series Turret, 5M 15fps, H.264/MJPEG, f2.8mm Fixed-focal Lens, D/N, IR 30m, SNV, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK08/Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F)
111 – Network Camera – Turret	IT833-HVW	VORTEX Premium Series Outdoor Vandal Fixed Turret, 5M 15fps, H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR/warm light 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-30°C ~ 55° C (-22°F ~ 131°F),Built-in microphone
111 – Network Camera – Turret	VIT04A-W	Chroma24 Flat-faced AI Dome, 4M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, smart hybrid illuminator 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
120 – Network Camera – Bullet	IB839-EHTV-v2	VORTEX Premium Series Outdoor Vandal Remote Bullet, 5M 15fps, H.264/MJPEG, f = 2.8~12 mm, D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-35°C ~ 50°C (-31°F ~ 122° F),Two-way audio,Built-in microphone
120 – Network Camera – Bullet	IB939-EHTV	VORTEX Premium Series Outdoor Vandal Remote Bullet, 8M 15fps, H.264/MJPEG, f = 4.3~9.8mm,D/N, IR 40m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-35°C ~ 50°C (-31°F ~ 122° F),Two-way audio,Built-in microphone
120 – Network Camera – Bullet	IB833-HV	VORTEX Premium Series Outdoor Vandal Fixed Bullet, 5M 15fps, H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature:-30°C ~ 55°C (-22°F ~ 131°F),Built-in microphone
120 – Network Camera – Bullet	IB9365-EHT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two- way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~60° C (-58° F ~ 140° F)
120 – Network Camera – Bullet	IB9365-HT-A	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P- iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/AC24V, I/O 2/2, Two- way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
120 – Network Camera – Bullet	IB9365-HT-A(12-40MM)	Outdoor Bullet, 2M 60fps, H.265/H.264/MJPEG, f12 ~ 40mm Motorized Lens, P-iris, IR 100m, SNV, WDR PRO, Smart Stream III, PoE/DC12V/AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
120 – Network Camera – Bullet	IB9365-EHTV-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f4 ~ 9mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/ NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
120 – Network Camera – Bullet	IB9367-EHT-v2	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9367-EHT-v2 (5-50mm)	Outdoor Vandal-proof Bullet, 2M 60fps, H.265/H.264/MJPEG, f2.7 ~ 13.5mm Motorized Lens, P-iris, D/N, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/ DC12V, I/O 1/1, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9368-HT	Outdoor Bullet, 2M 30fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
120 – Network Camera – Bullet	IB9369	2M 30fps, H.265/H.264/MJPEG, 2.8mm or 3.6mm,IR 30m, Smart motion,PoE/ DC12V, Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
120 – Network Camera – Bullet	IB9380-H	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
120 – Network Camera – Bullet	IB9387-EHT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -50° C ~ 60° C (-58° F ~ 140° F)
120 – Network Camera – Bullet	IB9387-HT-A	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
120 – Network Camera – Bullet	IB9388-HT	Outdoor Bullet, 5M 20fps, H.265/H.264/MJPEG, f2.8~12mm motorized lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)

120 – Network Camera – Bullet	IB9389-EH-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9389-EHT-v2	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, MicroSD/SDHC/SDXC, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9387-EHTV-V3(12-40MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 12-40mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9387-EHTV-V3(7-22MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9387-EHTV-V3(2.7-13.5MM)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, 3DNR, PoE/DC12V, I/O 1/1 by default, extra I/O 2/2 & AC 24V by external IO module, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Smart VCA, Vision Object Analytics, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB9391-EHTV-v2	Outdoor Vandal-proof Bullet, 4K 30fps, H.265/H.264/MJPEG, f4.4 ~ 10.2mm Motorized Lens, P-iris, D/N, IR 50m, SNV II, WDR PRO II, Smart Stream III, Smart IR III, 3DNR, PoE/DC12V/AC24V, I/O 3/3, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10/NEMA 4X, Working Temperature: -50°C ~ 60°C (-58°F ~ 140°F)
120 – Network Camera – Bullet	IB9383-HV	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F)
120 – Network Camera – Bullet	IB9383-HTV	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8~12mm remote focal lens, D/N, IR 30m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F)
120 – Network Camera – Bullet	IB9389-EHV-V3	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 3.0mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~
120 – Network Camera – Bullet	IB9389-EHTV-V3	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 3.3~9.7mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~
120 – Network Camera – Bullet	IB9399-EHV	Outdoor Bullet, 8M 30fps, H.265/H.264/MJPEG, 4.2mm Fixed Lens, Fixed-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~
120 – Network Camera – Bullet	IB9399-EHTV	Outdoor Bullet, 8M 30fps, H.265/H.264/MJPEG, 4.3~9.8mm Varifocal Lens, P-iris, IR 40m, TPM 2.0, RealSight engine, SNV, WDR PRO, Smart Stream III, 3DNR, PoE, Smart VCA, Vision Object Analytics, Two-way audio and Alarm I/O 1/1, MicroSD/SDHC/SDXC, IP66, IP67, IK10, NEMA 4X, Working Temperature: -35°C ~
120 – Network Camera – Bullet	IB9380-HTV-V2	AI Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7~13.5mm remote focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F)
120 – Network Camera – Bullet	IB9380-HV-V2	AI Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.8mm fixed focal lens, D/N, IR 30m, WDR Pro, Smart VCA, Two-way audio and Alarm I/O 1/1, PoE/DC, MicroSD/SDHC/SDXC, Working Temperature: -30°C ~ 60°C (-22°F ~ 140°F)
120 – Network Camera – Bullet	IB639	VORTEX Essential Series Outdoor Bullet, 2M 15fps, H.264/MJPEG, 2.8mm, D/N, IR 30m, WDR Enhance, Smart Stream III, 3DNR, PoE/DC12V, Built in Mic, Built-in 128G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
120 – Network Camera – Bullet	IB839-EH	VORTEX Essential Series Outdoor Bullet, 5M 15fps, H.264/MJPEG, f3.6mm fixed focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
120 – Network Camera – Bullet	IB839-EHT	VORTEX Essential Series Outdoor Bullet, 5M 15fps, H.264/MJPEG, f2.8~10mm remote focal lens, D/N, IR 30m, WDR Pro, 3DNR, PoE, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IK10/Working Temperature: -40°C ~ 60°C (-40°F ~
120 – Network Camera – Bullet	IB837-HT	VORTEX Premium Series (Powerful AI Search) Outdoor Bullet, 5M 15fps, H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 50m, SNV, WDR PRO, Smart Stream III, PoE/DC12V, I/O 2/2, Two-way Audio, Built-in 256G MicroSD Card (30 Days Edge Recording), IP66/IP67/IK10, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
130 – Network Camera – Fisheye Panoramic	FE9180-H-v2	Indoor, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, daytime only, WDR Pro, PoE, Built-in Mic, MicroSD/SDHC/SDXC
130 – Network Camera – Fisheye Panoramic	FE9192-H	Recessed Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC

130 – Network Camera – Fisheye Panoramic	FE9380-HV	Outdoor Vandal Proof, 5M, 30fps, H.265/H.264/MJPEG, f1.16mm fisheye lens, D/ N, IR 10m, WDR Pro, 3DNR, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp -30°C ~ 60°C / -22 °F ~ 140 °F
130 – Network Camera – Fisheye Panoramic	FE9382-EHV-v2	Outdoor Vandal Proof, 6M, 30fps, H.265/H.264/MJPEG, f1.245mm lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 55°C / -40 °F ~ 131 °F), DI/DO/ Audio Cable available by special order (PRR)
130 – Network Camera – Fisheye Panoramic	FE9191-H-v2	Indoor, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC
130 – Network Camera – Fisheye Panoramic	FE9391-EHV-v2	Outdoor Vandal Proof, 12M, 30fps, H.265/H.264/MJPEG, f1.22mm fisheye lens, D/N, WDR Pro, Smart IR II, 20m IR Illuminators, PoE, Built-in Mic, Smart Stream III, Smart VCA, MicroSD/SDHC/SDXC, IP66, IK10, NEMA 4X, extreme weather (-40°C ~ 60°C / -40 °F ~ 140 °F), DI/DO/ Audio Cable available by special order (PRR)
130 – Network Camera – Fisheye Panoramic	FE9391-EHV-v2 (1.18MM)	Outdoor 360 Fisheye, 12MP 2816x2816, 30fps, H.265/H.264/MJPEG, f1.18mm lens, F1.8, WDR Pro, 20m Smart IR, Built-in Mic, Optional DI/DO/2-way Audio, MicroSD/SDHC/SDXC, PoE, Smart VCA, IP66, IK10, NEMA 4X, Local Dewarp, NDAA, -40°C ~ 55°C;
130 – Network Camera – Fisheye Panoramic	FE9191-H-V2 (1.18MM)	Indoor 360 Fisheye, 12MP 2816x2816, 30fps, H.265/H.264/MJPEG, f1.18mm lens, F1.8, WDR Pro, Built-in Mic, MicroSD/SDHC/SDXC, PoE, Smart VCA, Local Dewarp, NDAA,IK10, -10°C ~ 50°C
130 – Network Camera – Fisheye Panoramic	FE912-H	VORTEX Premium Series (Powerful AI Search) Indoor Recessed 360 Fisheye, 12M (2944x2944), 15fps, H.264/MJPEG, f1.22mm fisheye lens, F1.8, Day/Night, WDR Pro, Local Dewarp, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), Smart Stream III, Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
130 – Network Camera – Fisheye Panoramic	FE931-EHV	VORTEX Premium Series (Powerful AI Search) Outdoor Vandal-proof 360 Fisheye, 12M (2944x2944), 15fps, H.264/MJPEG, f1.22mm fisheye lens, F1.8, Day/Night, WDR Pro, Local Dewarp, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), Smart Stream III, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
131 – Network Camera – Compact Panoramic	CC831-HV	VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 5MP 180° Panoramic, 15fps, H.264/MJPEG, f1.47 fisheye lens, Day/Night, 20M IR, WDR Pro, PoE, built-in mic, Built-in 256GB MicroSD Card(30 Days Edge Recording),IP66, IK10, operating temp (-
131 – Network Camera – Compact Panoramic	CC830-HV	VORTEX Premium Series (Powerful AI Search)Outdoor Vandal Dome, 5MP 180° Panoramic, 15fps, H.264/MJPEG, f1.47 fisheye lens, Day/Night, WDR Pro PoE, built-in mic, Built-in 256GB MicroSD Card(30 Days Edge Recording) IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F)
131 – Network Camera – Compact Panoramic	CC9160-H	Indoor, 2M 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.66mm, fisheye lens, Daytime, PoE, built-in mic, DI/DO, operating temp (-10°C ~ 45°C)
131 – Network Camera – Compact Panoramic	CC9160-H(HS)	Indoor, 2M 180° Panoramic height strip(feet, cm), 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C)
131 – Network Camera – Compact Panoramic	CC9160-H(DJ)	Indoor, 2M 180° Panoramic Door Jamb, 30fps, H.265/H.264/MJPEG, f1.66mm fisheye lens, Daytime, PoE, DI/DO, operating temp (-10°C ~ 45°C)
131 – Network Camera – Compact Panoramic	CC9380-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
131 – Network Camera – Compact Panoramic	CC9381-HV	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.45 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-20° C ~50° C/ -4°F ~ 122°F)
131 – Network Camera – Compact Panoramic	CC9391-HV	Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F)
131 – Network Camera – Compact Panoramic	CC9390-HV	Outdoor Vandal Dome, 8MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f2.53 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F)
131 – Network Camera – Compact Panoramic	CC9381-HV-V2	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~60° C/ -13°F ~ 140°F)
131 – Network Camera – Compact Panoramic	CC9380-HV-V2	Outdoor Vandal Dome, 5MP 180° Panoramic, 30fps, H.265/H.264/MJPEG, f1.47 fisheye lens, Day/Night, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, Smart VCA, Vision Object Analytics, IP66, IK10, operating temp (-30° C ~55° C/ -13°F ~ 131°F)
132 – Network Camera – Multi-directional Panoramic	MA9311-EHTV	Outdoor Vandal Dome, 10M Multi-Sensor Adjustable, (2x5M sensors), 30fps, H.265/H.264/MJPEG, 2.8~12mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 20m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131°F)

132 – Network Camera – Multi-directional Panoramic	MA9312-EHTV	Outdoor Vandal Dome, 16M Multi-Sensor Adjustable, (2x8M sensors), 30fps, H.265/H.264/MJPEG, 4.3~9.8mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 20m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131°F)
132 – Network Camera – Multi-directional Panoramic	MA9322-EHTV-V2	Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.2~7.7mm motorized lenses, D/N, WDR Pro 120dB, TPM 2.0, RealSight engine, Smart VCA, Vision Object Analytics, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 55°C/ - 40°F ~ 131°F)
132 – Network Camera – Multi-directional Panoramic	MA9322-EHTVL	Outdoor Vandal Dome, 20M Multi-Sensor Adjustable, (4x5M sensors), 30fps, H.265/H.264/MJPEG, 3.7~7.7mm motorized lenses, D/N, WDR Pro 120dB, 30m IR illuminators, PoE, Smart Stream III, operating temp. (-40°C ~ 50°C/ - 40°F ~ 122°F)
133 – Network Camera – Multi-sensor Panoramic	MS9390-HV-v2	Outdoor Vandal Dome, 8MP 180° Panoramic (2x4M sensors), 30fps, H.265/H.264/MJPEG, f2.8mm lenses, Day/Night, 180° IR Illuminators, WDR Pro 120dB, PoE, built-in mic, MicroSD/SDHC/SDXC, IP66, IK10, operating temp (-40° C ~55° C/ -40°F ~ 131° F)
133 – Network Camera – Multi-sensor Panoramic	MS9321-EHV-V2	Outdoor Vandal Bullet, 18MP 180° Panoramic, (4x5MP sensors), 30fps, H.265/H.264/MJPEG, Day/Night, 30m IR illuminators, WDR Pro 120 dB, Smart VCA, Vision Object Analytics, IP66, IK10, IP6K9K, operating temp. (-40°C ~ 55°C, -40°F ~ 131°F)
133 – Network Camera – Multi-sensor Panoramic	MS930-EHV	VORTEX Premium Series (Powerful AI Search) Outdoor Vandal Dome, 8M 180° Panoramic (4736x 1648), (2x4M sensors), 15fps, H.264/MJPEG, 2.8mm each lens, D/N, IR 20m, Smart IR III, WDR Pro, PoE, Built-in Mic, Built-in 512G MicroSD Card (30 Days Edge Recording), IP66, IK10, Operating Temp-40°C ~ 60°C (-40°F ~ 140°F)
140 – Network Camera – PTZ	SD9161-H-v2	Indoor Speed Dome, 2M 30fps, H.265/H.264/MJPEG, 10x Optical Zoom, WDR Pro, 3DNR, PoE/AC 24V/DC 48V, I/O*2/1, Two way audio, MicroSD/SDHC/SDXC
140 – Network Camera – PTZ	SD9384-EHL	IR Speed Dome, 5M 30fps, H.265, 30x Optical Zoom, IR 200M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
140 – Network Camera – PTZ	SD9368-EHL	IR Speed Dome, 2M 60fps, H.265, 40x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
140 – Network Camera – PTZ	SD9394-EHL	IR Speed Dome, 4K 30fps, H.265, 30x Optical Zoom, IR 250M, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA 4X
140 – Network Camera – PTZ	SD9387-EHL	Speed Dome, 5M 30fps, H.265, 30x Optical Zoom, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA
140 – Network Camera – PTZ	SD9367-EHL	Speed Dome, 2M 60fps, H.265, 40x Optical Zoom, WDR Pro, 3DNR, PoE/DC48V/AC24V, I/O*2/1, Two way audio, Micro SDXC, IP66, IK10, NEMA
150 – Network Camera – Box	IP9165-HT-v2	Box Camera, 2M 60fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
150 – Network Camera – Box	IP9181-HT-v2	Box Camera, 5M 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
150 – Network Camera – Box	IP9191-HT-v2	Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
160 – Network Camera – Transportation	MD8564-EH	Mobile Dome, 2M 30fps, H.264/MJPEG, f3.6mm fixed Lens, IR 15M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IP68, IK10, NEMA 4X, EN50155 TX
160 – Network Camera – Transportation	MD8564-EH-V2 (3.6 mm)	5MP, 3.6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 4pin D-coded PoE, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+, NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security
160 – Network Camera – Transportation	MD8564-EH-V2 (6 mm)	5MP, 6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 4pin D-coded PoE, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+, NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security
160 – Network Camera – Transportation	MD8564-DEH-V2 (6 mm)	5MP, 6mm, WDR Pro ,RAL9011, H.265, Smart Stream III, M12 5pin A-coded DC & 4pin D-coded PoE backup, 50 Meters IR Illumination, IP6K9K/IP67/IP68, IK10+, NEMA 4X, EN50155 OT4/ST1, Trend Micro IoT Security
160 – Network Camera – Transportation	MD9560-DH(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, DC power input, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
160 – Network Camera – Transportation	MD9560-H(2.8MM,HL1)	Mobile Dome, 2M 30fps, H.265, f2.8mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
160 – Network Camera – Transportation	MD9560-H(3.6MM,HL1)	Mobile Dome, 2M 30fps, H.265, f3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built- in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT1, EN45545 HL1
160 – Network Camera – Transportation	MD9582-H	Mobile Dome, 5M 30fps, H.265, f2.8mm or 3.6mm fixed Lens, 3Axis, 850nm IR 20M, WDR Pro, 3DNR, M12, PoE, I/O*1/1, One way audio, Built-in Microphone and Line in, MicroSD/SDHC/SDXC, IP67, IK10, NEMA 4X, EN50155 OT4, EN45545 HL1 or HL3
160 – Network Camera – Transportation	MD9584-H	Mobile Dome, 5M 30fps, H.265, f3.6mm fixed Lens, 850nm IR 50M, WDR Pro, M12, PoE, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, IP6K9K, IK68, IK10+, NEMA 4X, EN50155 OT4, EN45545 HL3
160 – Network Camera – Transportation	SC8132	Stereo People Counting Network Camera, dual image sensors, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240 cm (6.2~7.9')

160 – Network Camera – Transportation	SC8133	Stereo People Counting Network Camera, dual image sensors, white LED, H.264/MJPEG, Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Working Temperature: -25°C ~ 55°C (-13°F ~ 131°F), Installation Height: 190~240cm (6.2~7.9')
160 – Network Camera – Transportation	SC9133-RTL	AI Counting Network Camera for Retail, Deep Learning AI Counting, 140° Fiseye FOV for Better Coverage, Flexible Installation Height 2.4 to 10 m
160 – Network Camera – Transportation	MD9560-H-V2(2.4 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
160 – Network Camera – Transportation	MD9560-H-V2(2.8 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
160 – Network Camera – Transportation	MD9560-H-V2(6 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
160 – Network Camera – Transportation	MD9560-H-V2(2.8 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
160 – Network Camera – Transportation	MD9560-DH-V2 (2.8 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
160 – Network Camera – Transportation	MD9560-DH-V2 (3.6 mm)	Mobile Dome, EN50155 Rail-certified, 2M 60fps, H.265/H.264/MJPEG, fixed focal lens, D/N, IR 20m, WDR Pro, PoE, MicroSD/SDHC/SDXC, Working Temperature: -25°C ~
161 – Network Camera – Thermal	TB9332-E	TB9332-E is an outdoor AI thermal camera with 640x512 thermal resolution @ F1.0, 25fps, NETD < 40mK, with an option of 9mm, 15mm, 35mm & 50mm lens, temperature measurement alarms, VCA suite ((Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, Enter, Leave), object classification (person/ vehicle), smoker detection, fire spot detection, Alarm I/O, Two-way audio, IP66, NDAA Compliant
161 – Network Camera – Thermal	TB9333-E	TB9333-E is an outdoor bi-spectrum AI thermal bullet cameras with 256x192 thermal @ F1.0 and 4MP visible resolution, 30fps, NETD < 50mK, with options of 3.5mm thermal lens & 4mm visible lens, or 7mm thermal lens & 8mm visible lens, temperature measurement alarms, VCA suite ((Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, Enter, Leave), Object classification (person/ vehicle), smoker detection, fire spot detection, smoke & flame detection, Alarm I/O, Two-way audio, IP66, NDAA Compliant
161 – Network Camera – Thermal	TT9333-E	TT9333-E is an outdoor bi-spectrum AI thermal turret cameras with 256x192 thermal @ F1.0 and 4MP visible resolution, 30fps, NETD < 50mK, with options of 3.5mm thermal lens & 4mm visible lens, or 7mm thermal lens & 8mm visible lens, temperature measurement alarms, VCA suite ((Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, Enter, Leave), Object classification (person/ vehicle), smoker detection, fire spot detection, smoke & flame detection, Alarm I/O, Two-way audio, IP66, NDAA Compliant
162 – Network Camera – Application	FD9387-FR-v2	5MP, Short Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II
162 – Network Camera – Application	FD9387-FR-v3	5MP, Mid Range Facial Recognition Camera, H.265, Up to 10,000 Facial Profiles, WDR Pro, SNV, 50M IR, Smart IR II
162 – Network Camera – Application	IB9387-LPR-v2	License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/ AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
162 – Network Camera – Application	IB9387-LPR-v2-W	License Plate Recognition Bullet, 5M 30fps, H.265/H.264/MJPEG, f2.7 ~ 13.5 Motorized Lens, P-iris, IR 2~6m, SNV, WDR PRO, Smart Stream III, PoE/ DC12V/ AC24V, I/O 2/2, Two-way Audio, MicroSD/SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), Working Temperature: -30° C ~ 60° C (-22° F ~ 140° F)
162 – Network Camera – Application	VC9101	Video Core, split-type, H.265,H.264/MJPEG, PoE/DC 8-36V, I/O*1/1, Two way audio, MicroSD/SDHC/SDXC, operating temp(-10°C ~ 50°C); work with camera unit (CU series)
162 – Network Camera – Application	SC8131	Stereo People Counting Network Camera, dual image sensors, lens f = 2mm, H.264/ MJPEG, Starting Temperature: 0°C ~ 40°C (32°F ~ 104°F), Working Temperature: -10°C ~ 40°C (14°F ~ 104°F), Installation Height: 240~500 cm (7.9~16.4')
162 – Network Camera – Application	SC9133	Deep Learning AI Counting Network Camera, Deep Learning AI Detection* for Passenger Classification, White LEDs for Low Lighting Counting, EN50155
162 – Network Camera – Application	IB9387-LPR-V3(2.7-13.5MM) (N)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VIVOTEK ANPR, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
162 – Network Camera – Application	IB9387-LPR-V3(2.7-13.5MM) (V)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VaxALPR, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
162 – Network Camera – Application	IB9387-LPR-V3(7-22MM) (N)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 7-22mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, , EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VIVOTEK ANPR, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)

162 – Network Camera – Application	IB9387-LPR-V3(7-22MM) (V)	Outdoor Bullet, 5M 30fps, H.265/H.264/MJPEG, 2.7-13.5mm Motorized Lens, P-iris, Built-in IR illuminators, IR LED*4, SNV, WDR PRO, Smart Stream III, 3DNR, , EIS (built-in gyro sensor), scene mode (LPC-parking lot), PoE/AC24V/DC12V, I/O 2/2, Two-way Audio, MicroSD/ SDHC/SDXC, IP66/IP67/IK10 (Metal Housing), VaxALPR, Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
162 – Network Camera – Application	IP9165-LPC-v2	License plate capture, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
162 – Network Camera – Application	IP9165-LPR-v2 Kit (Street)	License plate recognition kit, Box Camera, 2M 60fps, H.265/H.264/MJPEG, i-CS supported, manual focus, D/N, SNVII, WDR PRO II, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, Snap-in IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
162 – Network Camera – Application	IP9181-LPC-v2	License plate capture, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
162 – Network Camera – Application	IP9181-LPC-v2 (Kit)	License plate capture kit, Box Camera, 5M 30fps, H.265/H.264/MJPEG, i-CS supported, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio, External IR Illuminator, IP68/IK10, Working Temperature: -40° C ~60° C (-40° F ~ 140° F)
162 – Network Camera – Application	IP9191-LPC-v2	License Plate Capture, Box Camera, 4K 30fps, H.265/H.264/MJPEG, remote back focus, D/N, SNV, WDR PRO, 3DNR, Smart stream III, PoE/DC12V/AC24V, I/O 2*2, RS485, 2way audio
200 – NVR – Embedded	ND9213P	H.265, 4CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 4/2 alarm in/out, 1HDD, 1 LAN(FE), 4 PoE, NDAA
200 – NVR – Embedded	ND9323P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 8 PoE
200 – NVR – Embedded	ND9425P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 120 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE
200 – NVR – Embedded	ND9442P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
200 – NVR – Embedded	ND9542P	H.265, 32CH, 1 HDMI+1 VGA, 1080P @ 360 fps, 4K display, 16/8 alarm in/out, 4 HDD, RAID 0/1/5, 2 LAN(Giga), 16 PoE, Core+ AI
200 – NVR – Embedded	ND9326P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 2 LAN(Giga), 8 PoE, Core+ AI
200 – NVR – Embedded	ND9426P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @ 480 fps, 4K display, 2 HDD, RAID 0/1, 1 LAN(Giga), 16 PoE, Core+ AI
201 – NVR – Recording Server	NR9581-v2	H.265, 32CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
201 – NVR – Recording Server	NR9681-v2	H.265, 64CH, 1 HDMI+ 1 DP, 1080P @ 270 fps, 8 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, Redundant Failover server, VAST2
201 – NVR – Recording Server	NR9682-v2	H.265, 64CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
201 – NVR – Recording Server	NR9782-v2	H.265, 128CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10, 2 LAN(Giga), Redundant power, version 2
201 – NVR – Recording Server	NR9581-v3	H.265, 32CH(expandable to 128CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 8 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro
201 – NVR – Recording Server	NR9682-v3	H.265, 64CH(expandable to 192CH), 1 HDMI+1 DP+ 1 DVI +1 VGA, 1080P @180 fps, 4K display, 16 Hot-swappable HDD, RAID 0/1/5/6/10/50/60, 2 LAN(2.5 Giga), Redundant power, VSS Pro
202 – NVR – CMS Station	NS9521	H.265, 32CH, 1 HDMI+1 DP+ 1 DVI, 1080P @ 270 fps, 4K display, 2 HDD, 2 LAN(Giga), VAST2 Station
203 – NVR – Mobile NVR	NV9321P	H.265, 8CH, 1 HDMI+1 VGA, 1080P @360 fps (12-CH) or 3840x2160 @90 fps (3-CH), swappable Dual SSD, RAID 0/1, 802.3at/af compliant PoE ports x 8 (M12)
203 – NVR – Mobile NVR	NV9421P	H.265, 16CH, 1 HDMI+1 VGA, 1080P @360 fps (12-CH) or 3840x2160 @90 fps (3-CH), swappable Dual SSD, RAID 0/1, 802.3at/af compliant PoE ports x 8 (M12)
310 – PoE – Unmanaged Switch	AW-FET-060C-065	4xFE POE +2FE UTP Switch
310 – PoE – Unmanaged Switch	AW-FGT-100D-120	8xFE PoE + 2xGE Combo Switch
310 – PoE – Unmanaged Switch	AW-FGT-180D-250	16xFE POE +2G COMBO Switch
310 – PoE – Unmanaged Switch	AW-FGT-260D-380	24xFE POE +2G COMBO Switch
310 – PoE – Unmanaged Switch	AW-GET-050A-065,USA	4xGE POE + 1xGE SWITCH
310 – PoE – Unmanaged Switch	AW-GET-100A-120,USA	8XGE POE + 2XG SFP SWITCH
310 – PoE – Unmanaged Switch	AW-FET-060D-065	4xFE PoE + 2xFE RJ45 Unmanaged Switch, Power Budget 65W
310 – PoE – Unmanaged Switch	AW-FGT-180F-250	16xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 250W
310 – PoE – Unmanaged Switch	AW-FGT-260F-380	24xFE PoE + 2xGbE Combo Unmanaged Switch, Power Budget 380W
310 – PoE – Unmanaged Switch	AW-FET-060P-060	4xFE PoE + 2xFE RJ45 Switch
310 – PoE – Unmanaged Switch	AW-FGT-100P-110	8xFE PoE + 2xGbE Combo Switch
310 – PoE – Unmanaged Switch	AW-FGT-180P-250	16xFE PoE + 2xGbE Combo Switch
310 – PoE – Unmanaged Switch	AW-FGT-260P-370	24xFE PoE + 2xGbE Combo Switch

311 – PoE – Managed Switch	AW-GEV-104B-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 130W) Integrate with VIVOTEK Camera for surveillance application
311 – PoE – Managed Switch	AW-GEV-107A-130,USA	8-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 130W) Integrate with VIVOTEK Camera for surveillance application
311 – PoE – Managed Switch	AW-GEV-184B-250,USA	16-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 250W) Integrate with VIVOTEK Camera for surveillance application
311 – PoE – Managed Switch	AW-GEV-264B-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE SFP Web Smart Managed PoE Switch (PoE Output Power Max. 370W) Integrate with VIVOTEK Camera for surveillance application
311 – PoE – Managed Switch	AW-GEV-267A-370,USA	24-Port GbE RJ45(PoE) +2-Port GbE RJ45/SFP + 1-Port RJ45 Console VivoCam Layer 2 Plus Managed PoE Switch (PoE Power Budget Max. 370W) Integrate with Vivotek Camera for surveillance application
311 – PoE – Managed Switch	AW-GTS-287A,USA	24xGE SFP + 4xCombo GE + 4x 10G SFP+ L2 Plus Managed Switch
311 – PoE – Managed Switch	AW-GEV-108A-130	VIVOCAM L2 Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 2xGbE Combo + 1xRJ45 console port, Power Budget 130W
311 – PoE – Managed Switch	AW-GEV-288A-370	VIVOCAM L2 Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 4xGbE Combo + 1xRJ45 Console port, Power Budget 370W
311 – PoE – Managed Switch	AW-GEL-065A-060	Lite Managed PoE Switch 4xGbE PoE + 2xGbE RJ45, Power Budget 60W
311 – PoE – Managed Switch	AW-GEL-105A-110	Lite Managed PoE Switch 2xGbE bt 90W PoE + 6xGbE af/at 30W PoE + 1xGbE RJ45 + 1xGbE SFP, Power Budget 110W
311 – PoE – Managed Switch	AW-GEL-205A-260	Lite Managed PoE Switch 4xGbE bt 90W PoE + 12xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 260W
311 – PoE – Managed Switch	AW-GEL-285A-380	Lite Managed PoE Switch 4xGbE bt 90W PoE + 20xGbE af/at 30W PoE + 2xGbE RJ45 + 2xGbE SFP, Power Budget 380W
312 – PoE – Optical Transceiver	SFP-1000-CPTX-X1	Gigabit SFP to RJ45 Module
312 – PoE – Optical Transceiver	SFP-1000-CPTX-X1I	Industrial Gigabit SFP to RJ45 Module
312 – PoE – Optical Transceiver	SFP-1000-MM13-02	Gigabit Mini GBIC Multi Mode 1310nm 2KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-MM13-02I	Industrial Gigabit Mini GBIC Multi Mode 1312nm 2KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-MM85-X5	Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-MM85-X5I	Industrial Gigabit Mini GBIC Multi Mode 850nm 0.5KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-SM13-10	Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-SM13-10I	Industrial Gigabit Mini GBIC Single Mode 1312nm 10KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-SM13-40	Gigabit Mini GBIC Single Mode 1310nm 40KM, LC Connector
312 – PoE – Optical Transceiver	SFP-1000-SM13-40I	Industrial Gigabit Mini GBIC Single Mode 1312nm 40KM, LC Connector
312 – PoE – Optical Transceiver	SFP-2000-MM85-X3	10 Gigabit Mini GBIC Multi Mode 850nm 0.3KM, LC Connector
312 – PoE – Optical Transceiver	SFP-2000-SM13-10	10 Gigabit Mini GBIC Single Mode 1310nm 10KM, LC Connector
320 – PoE – Industrial	AW-IHH-0800	Industrial 4xGE 95W PoH/PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 95W, Power budget 240W, 54~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-0800	Industrial 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 120W, 48~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-1000	Industrial 8xGE PoE + 2xGE SFP Switch, Per PoE port up to 30W, Power budget 240W, 48~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-1271	Industrial VivoCam L2+ Managed PoE Switch 8xGE PoE + 4xGE SFP Per PoE port Max. 30W, power budget 240W, 48~57VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHH-0110	Industrial Gigabit 95W POH/POE Injector Industrial Gigabit 95W POH Injector, 48-56VDC input, -40° C to +75° C
320 – PoE – Industrial	AW-IHS-0202	Industrial Media Convert SFP True Mini Industrial Media Converter, 10/100M RJ45 to 100M SFP, Designed for outdoor CAM enclosure, Din-Rail mount and Panel mount, 18-36VAC/12- 60VDC, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-0100	Industrial Gigabit 30W POE Injector Industrial Gigabit 30W POE Injector, 48-56VDC input, -40° C to +75° C
320 – PoE – Industrial	AW-IHT-0200	Industrial 1xGE PoE + 1xGE SFP Switch 1 port 802.3at 30W POE 10/100/1000M + 1 port 100/1000M SFP, 48~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHH-0410	Industrial 2xGE 95W POH/POE + 2xGE SFP Switch, 48~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-0601	Industrial 4XGE POE+2XGE SWITCH SFP 12V-56V Super Voltage Booster 12~56VDC input, 4 port 802.3at 30W POE 10/100/1000M + 1 port 10/100/1000M SFP/TX Combo + 1 port 100/1000M SFP, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-0602	Industrial EN50155 4xFE M12 PoE + 2xFE M12 Switch 4 port 802.3at 30W POE M12 10/100M + 1 port M12 10/100M, 24~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHB-0100	Industrial Gigabit 802.3bt 90W PoE injector, 48-56VDC input, -40° C to +75° C
320 – PoE – Industrial	AW-IHB-0400	Industrial 2xGE 802.3bt 90W PoE + 2xGE SFP Switch, power budget 180W, 48~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHB-0800	Industrial 4xGE 802.3bt 90W PoE + 2xGE UTP + 2xGE SFP Switch, power budget 360W, 54~56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHB-1040	Industrial Lite Managed PoE Switch 2xGbE bt 90W + 6xGbE af/at 30W + 2xGbE SFP, Power budget 300W, 48-56VDC input, -40° C to 75° C
320 – PoE – Industrial	AW-IHT-1002	Industrial M12 PoE Switch 8xFE D-coded PoE + 2xGbE X-coded, EN50155/EN45545-2, -40° C to 75° C

321 – PoE – Extender	AP-FXC-0110	1-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C
321 – PoE – Extender	AP-FXC-0160	1-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-FXC-0210	2-port Indoor 95/60/30 W PoE Extender Supported PSEs providing 95W/60W/30W PoE 0° C ~ 50° C
321 – PoE – Extender	AP-FXC-0260	2-port Outdoor 95/60/30 W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-GXC-0150	1-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-GXC-0250	2-port gigabit Outdoor 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-GXC-0100	1-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 95W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-GXC-0200	2-port gigabit 802.3bt 90/60/30W PoE Extender; IP67 Supported PSEs providing 90W/60W/30W PoE -40° C~ 65° C
321 – PoE – Extender	AP-FXC-0400	4-Port indoor FE PoE Extender
321 – PoE – Extender	AP-FHP-0100-R	Hyper PoE PoE in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C
321 – PoE – Extender	AP-FHP-0105-R,USA	Hyper PoE DC in Rx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C AA-420, US power cord
321 – PoE – Extender	AP-FHP-0105-T	Hyper PoE Tx, 1x Hyper PoE Port, 1x FE RJ45, 1 DC Jack, -20° C~60° C
322 – PoE – Injector	AP-FIC-010A-015,USA	Indoor IEEE802.3af FE PoE Injector
322 – PoE – Injector	AP-GIC-010A-030,USA	Indoor IEEE802.3at Gigabit PoE Injector
322 – PoE – Injector	AP-GIC-011A-060,USA	Indoor Gigabit PoH 60W Injector
322 – PoE – Injector	AP-GIC-011A-095,USA	Indoor Gigabit PoH 95W Injector
322 – PoE – Injector	AP-GIC-015B-095	outdoor Gigabit PoH 95W Injector
322 – PoE – Injector	AP-GIC-011A-030	Indoor Gigabit IEEE 802.3at 30W PoE Injector
322 – PoE – Injector	AP-GIC-011B-090	Indoor Gigabit IEEE 802.3bt 90W PoE Injector
330 – PoE – Cabinet	AT-CAB-001	Cabinet IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory device s such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover is included.
330 – PoE – Cabinet	AT-CAB-002	Side-mount bracket for HLG series power supply Protects accessory devices such as 120W power supply.
330 – PoE – Cabinet	AT-CAS-001	Cabinet for Speed dome IP66, IK10 outdoor-ready surveillance cabinet. Protects accessory device s such as power supply, media converter, Industrial PoE switch and power safety from tough weather and vandalism.Mounting bracket for wall, DIN- rail, cover
330 – PoE – Cabinet	AT-DRB-001	Cabinet industrial 95W PoE switch AW-IHH-0800 bracket
330 – PoE – Cabinet	AT-PSP-001	PoE Surge Protector: 8-10KA AT-PSP-001 is a surge protection device to provide Signal/Power path and surge protection capability. It employed our patented surge blocker wit h shunt devices and parallel devices to guarantee the safety of your dev ice, ev
330 – PoE – Cabinet	AT-SUN-001	Sunshield for AT-CAx series cabinet Metal sunshield for Vivotek Cabinet series. Reduces the temperature insi de the cabinet, caused by sun radiation.
330 – PoE – Cabinet	AT-SUN-002	Sunshield for AT-CAx + AT-CAB-002 cabinet Metal sunshield for BOTH Vivotek Cabinet and DC Power cabinet. Reduces the temperature inside the cabinet, caused by sun radiation.
330 – PoE – Cabinet	AT-SWH-000	Power Safety Kit (100~275VAC): 20-40KA Electrical safety kit for Vivotek Cabinet in countries where the mains p ower is 275V AC. Included products: Surge protector class 2, Fuse/main switch, terminal b locks and an intrusion door switch.
330 – PoE – Cabinet	AT-SWH-002	Door open/close detection switch Intrusion door switch for Vivotek Cabinet, connection to I/O port.
330 – PoE – Cabinet	AT-WPC-001	Cable gland M16 CABLE GLAND 4~7mm AWG 6PCS
330 – PoE – Cabinet	AT-WPC-002	Cable gland M16 CABLE GLAND for Corrugated Tubing : 5/16 " 6PCS
330 – PoE – Cabinet	AP-PSP-050	Outdoor PoE Surge Protector 16KV surge Operating temperature from -40° C to 85° C
330 – PoE – Cabinet	AW-GEH-043A-120	Outdoor Unmanaged 2xGE 95W PoH/PoE + 2xGE SFP Switch, Per PoE port max. 95W, power budget 120W, IP67, IK10
330 – PoE – Cabinet	AW-GET-083A-120	Outdoor Unmanaged 4xGE PoE + 2xGE UTP + 2xGE SFP Switch, Per PoE port max. 30W, power budget 120W, IP67, IK10
330 – PoE – Cabinet	AW-GEU-086A-240	Outdoor VivoCam L2+ Managed 4xGE UPoE + 2xGE UTP + 2xGE SFP Switch, Per PoE Port max. 60W, power budget 240W, IP67, IK10
331 – PoE – Power Supply	HLG-120H-24	90~305VAC In ,24VDC/120Wut ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-120H-48	90~305VAC In ,48VDC/120W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-120H-54	90~305VAC In ,54VDC/120W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-240H-54	90~305VAC In ,54VDC/240W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-60H-24	90~305VAC In ,24VDC/60Wut ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-80H-24	90~305VAC In ,24VDC/80W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-80H-48	90~305VAC In ,48VDC/80W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	HLG-80H-54	90~305VAC In ,54VDC/80W Out ,IP67, - 40 °C ~ 70 °C
331 – PoE – Power Supply	NDR-120-48	90~264VAC In, 48VDC/120W Out , - 20 °C ~ 70 °C
331 – PoE – Power Supply	NDR-240-48	90~264VAC In, 48VDC/240W Out , - 20 °C ~ 70 °C

331 – PoE – Power Supply	NDR-75-48	90~264VAC In, 48VDC/75W Out , - 20 °C ~ 70 °C
331 – PoE – Power Supply	DRL-48V120W1EN	90~264VAC In, 48VDC/120W Out , - 30 °C ~ 70 °C
331 – PoE – Power Supply	DRL-48V240W1EN	90~264VAC In, 48VDC/240W Out , - 30 °C ~ 70 °C
340 – PoE – EPoC	AM-713-E_V01	Conduit box with EPoC Tx module for Outdoor fixed dome
340 – PoE – EPoC	AP-FEX-0100-R	EPoC PoE in Rx Module, 1x BNC, 1x FE RJ45, -20 ° C~60 ° C
340 – PoE – EPoC	AP-FEX-0105-D,USA	EPoC Extender DC kit, AP-FEX-0105-R + AP-FEX-0105-T + AA-420, USA
340 – PoE – EPoC	AP-FEX-0105-P	EPoC Extender PoE kit, AP-FEX-0100-R + AP-FEX-0105-T
340 – PoE – EPoC	AP-FEX-0105-R,USA	EPoC DC in Rx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C, AA- 420,
340 – PoE – EPoC	AP-FEX-0105-T	EPoC DC in Tx Module, 1x BNC, 1x FE RJ45, 1 DC Jack, -20 ° C~60 ° C
340 – PoE – EPoC	AP-FEX-0150-T	EPoC Outdoor Tx Module, 1x BNC, 1x FE RJ45, -40 ° C~60 ° C, IP67, IK10
340 – PoE – EPoC	AP-FEX-0200-T	EPoC Tx Module, 1x BNC, 2x FE RJ45, -20 ° C~60 ° C
340 – PoE – EPoC	AP-FEX-0250-T	EPoC Outdoor Tx Module, 1x BNC, 2x FE RJ45, -40 ° C~60 ° C, IP67, IK10
340 – PoE – EPoC	AT-BSP-001	Coax surge protector for EPoC modules
340 – PoE – EPoC	AW-FCT-050A-250,USA	4xFE BNC + 1x GE RJ45 unmanaged EPoC switch, USA
410 – Accessory – Enclosure	AE-238	Side Open Aluminum Camera Housing AC24V in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
410 – Accessory – Enclosure	AE-239	Side Open Aluminum Camera Housing PoE in,Window heater,Fan,IP68, -20~50°C ,wall bracket&sun shield
410 – Accessory – Enclosure	AE-243	Side Open Aluminum Camera Housing, AC24V in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
410 – Accessory – Enclosure	AE-244	Side Open Aluminum Camera Housing, PoE in, Window heater, Fan,IP68, -20~50°C , 6W fixed IR, Wall Bracket, Sun shield
410 – Accessory – Enclosure	AE-23A	Side Open Aluminum Camera Housing AC24V in,Window heater, Fan,IP68, -20~50°C , optional snap-in VAIR,Wall bracket, Sun shield
410 – Accessory – Enclosure	AE-23E-v2	Side Open Aluminum Camera Housing, PoE in (BT), Window heater, Fan, IP68, -20~65 °C , optional snap-in VAIR, Wall bracket, Sun shield
411 – Accessory – CaMate	CA8018-1040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
411 – Accessory – CaMate	CA8018-2040	IR illuminator with CVA, 10°~ 40°, 140~350m, remote control, 80w
411 – Accessory – CaMate	CM3218-010	IR illuminator fixed IR 10°,180m, 32w
411 – Accessory – CaMate	CM3218-035	IR illuminator fixed IR 35°,60m, 32w
411 – Accessory – CaMate	CM4818-1040	IR illuminator with CVA, 10°~ 40°, 100~250m, 48w
411 – Accessory – CaMate	CM4818-180	IR illuminator with CVA, 180°, 40m, 48w
411 – Accessory – CaMate	CM4818-2040	IR illuminator with CVA, 20°~ 40°, 120 ~ 200m, 48w
411 – Accessory – CaMate	CM4818-4080	IR illuminator with CVA, 40°~ 80°, 60~90m, 48w
411 – Accessory – CaMate	CM4818-90120	IR illuminator with CVA, 90°~ 120°, 45~55m, 48w
412 – Accessory – Network Audio Devices	AU-003	IP Audio, AU-003, PoE network horn speaker
412 – Accessory – Network Audio Devices	AU-004	IP Audio, AU-004, PoE network ceiling speaker
501 – Facial Recognition	FT9361-R	Facial Recognition Access Control Tablet, Linux OS, Memory: 8GB ROM 1GB RAM, Max. 50,000 profiles, 1080P camera, 1440x720 display, PoE Class 4/DC 12V, Weigand
501 – Facial Recognition	IE9281-FM	Content Management System Support up to 256 Devices in One Single Server Support of Local Display via HDMI Easy to Integrate into Your System Rich Infographic Reports Support Rackmount Installation
501 – Facial Recognition	IE9232-F	Mask Detection and Recognition Enroll a Person's Profile with up to 5 Pictures Real-time Notifications and Alerts Persons of Interest (POI) Management Comprehensive Reports Support up to 6 Cameras/Servers