



# RX9401

## H.265 16-CH Embedded Video Receiver



### 技術規格

#### Technical Specifications

Descriptions	16-CH Embedded Video Decoder
--------------	------------------------------

#### Device

OS	Embedded Linux
Watchdog	硬體 + 軟體
Power Restoration	於電力恢復後自動重新啟動系統

#### Display

LiveView Display	16 路 多重影像配置顯示器： 1x1, 2x2, 3x3, 1P+3, 2P+3, 1M+5, 1P+6, 3V, 1M+12, 4x4
Video Output	HDMI x1
Display Resolution	3840x2160, 1920x1080, 1280x720
Stream Application	Constant\Auto Adaptive Stream
Fisheye Dewarp	10, 1P, 1R, 1O3R, 1O8R
PTZ Operation	方向控制、原位、預設、巡視 (群組設定)

#### Video

Video Format	H.264, H.265
Graphic Decoder	硬體解碼
Decoding Resolution	最高可達 3840x2160
Decoding Capability	3840x2160 @ 30 fps (1CH) 1920x1080 @ 120 fps (4CH) 720x480 @ 480fps (16CH)

#### Audio

Audio Format	G.711, G.726
--------------	--------------

Network	
Ethernet	10/100Mbps 乙太網路 (RJ-45) x 1
Network Throughput in total	40 Mbps
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter

External Interface	
USB	前: 1 (USB 2.0) 後: 1 (USB 2.0)

System	
Camera Integration	ONVIF core spec 2.2 or above (*by project)
User Management	使用者等級：系統管理員、一般使用者
Date&Time	時區、手動、自動同步 NTP、日光節約時間
Language	Czech, English, French, German, Italian, Japanese, Korean, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Traditional Chinese

Remote Client	
Software AP	Shepherd ,VAST 2(reserved)
Web Browser	Internet Explorer 10 (32 bit) or above

General	
Power Input	DC 12V 1.5A
Power Consumption	Max. 9.24 W
Dimensions	198 (W) x 200 (D) x 47(H)mm
Weight	530 g
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0 ~ 95%
Safety Certifications	CE, FCC, VCCI, C-Tick