



## V Series

# IP9191-HT-V2 (No-Lens)

8MP Box AI Camera



## Technical Specifications

### System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	8GB eMMC
RAM	2GB

### Camera Specifications

Image Sensor	1/1.8" Progressive CMOS
Max. Resolution	3840 x 2160 (16:9) 1920x1080p (16:9)
Iris Type	DC-iris, P-iris, i-CS
Shutter Time	1/1~1/100000
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Minimum Illumination	0.02 lux @ F1.5 (Color) 0.005 lux @ F1.5 (B/W)
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card and recording to network-attached storage (NAS)
Built-in Installation Aids	Remote back focus, BNC (CVBS)* *only 2MP mode available

### Video

Compression	H.265,H.264, MJPEG
Maximum Frame Rate	30 fps @ 3840x2160 (WDR Pro on) 60 fps @ 1920x1080 (WDR Pro off)

Maximum Streams	3 simultaneous streams (Up to 8 configurable profiles)
Main Stream	30fps @ 3840x2160, 3328x1872, 3072x1728, 2688x1520, 2560x1920, 2560x1440 (16:9); 60fps @ 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9)
2nd Stream	30fps @ 3840x2160, 3328x1872, 3072x1728, 2688x1520, 2560x1920, 2560x1440, 1920x1080, 1280x720, 640x360 (16:9); 60fps @ 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9)
3rd Stream	30fps @ 1280x720, 640x360 (16:9); 60fps @ 1280x720, 640x360 (16:9)
S/N Ratio	60 db
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constrained bit rate control, Smart Stream III
Image Settings	<p>General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings</p> <p>Illuminators illuminators, anti-overexposure</p> <p>Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, HLM,LDC, EIS*, scene mode (auto, deblur)</p> <p>Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR</p> <p>Focus zoom, focus</p> <p>Privacy mask Scheduled profile settings</p>

Audio	
Audio Capability	Two-way Audio
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	External microphone input External line output

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Account block , Audit log, Configurable password strength protection, CSRF protection, Digest authentication, HTTPS , IEEE 802.1x, Secure boot, Session timeout, Signed firmware, Trend Micro IoT Security (Brute force attack event, Cyberattack event, Quarantine event), User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, SFTP, TCP/IP, TLS 1.2, UDP, UPnP
Interface	10 Base-T/100 Base-TX/1000 Base-T Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator

Vision Object Analytics	<p>Object Detection people, vehicle (4-wheeled, 2-wheeled)</p> <p>Attribute Extraction people (gender, color, bag, hat), vehicle (bike, bus, car, motorcycle, truck, color)</p> <p>Re-Search Extraction Path Extraction</p>
Application	<p>Deep Learning VCA (Smart Motion Detection) Smart VCA with i-CS lens Smart VCA (Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, Unattended object detection, Missing object detection, Crowd detection) Smart VCA with non i-CS lens Smart VCA (Smart VCA (Intrusion detection, Loitering detection, Line crossing detection)</p>
Application available with license	<p>Running detection, Parking Violation Detection, Restricted Zone Detection Support for more analytic applications and free trial, please visit <a href="http://vivotek.com/video-analytics">vivotek.com/video-analytics</a></p>

## Solution Integration

VADP Package	Trend Micro IoT Security (Default 3 years)
--------------	--

## Alarm and Event

Event Trigger	<p>Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), digital input, manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot, Casing open detection</p>
Event Action	<p>Event notification via audio clip, camera link, digital output, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card</p>

## General

Supported P/T/Z	DynaDome/SmartDome, Pelco D, Pelco P, Lilin, Samsung scc643 and customized
Connectors	<p>RJ-45 cable connector for 10/100/1000Mbps Network/PoE connection Audio input Audio output AC 24V power input *1 DC 12V power input*1 Digital input *2 Digital output *2 (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A) RS485*1 BNC *1</p>
LED Indicator	System power and status indicator
Power Input	AC 24V, DC 12V, IEEE 802.3af PoE Class 0
Power Consumption	<p>DC 12V: Max. 8.88 W AC 24V: Max. 17 W PoE: Max. 10 W</p>
Dimensions	<p>155 (D) x 70 (W) x 61 (H) mm (w/o lens) 210 (D) x 70 (W) x 66 (H) mm (w/ lens)</p>
Weight	<p>680 g (w/o lens) 790 g (w/ lens)</p>
Certifications	CE, LVD, FCC Class B, VCCI, C-Tick, UL/CUL, BIS, BSMI
Operating Temperature	<p>Start Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working temperature: -10°C ~ 60°C (14°F ~ 140°F)</p>
Humidity	90% (non-condensing)

## System Requirements

Operating System	<p>Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)</p>
------------------	---

Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

Included Accessories	
Packing Contents	Quick installation guide, screw pack